

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Rhepanol-Dachfarbe Kupfer

Revision date: 02.03.2018

Product code: RCSO-FDT-041

Page 1 of 12

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Rhepanol-Dachfarbe Kupfer

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

coating

Uses advised against

Only use for the intended purpose.

The product is intended for professional use.

1.3. Details of the supplier of the safety data sheet

Company name:	FDT Flachdach Technologie GmbH & Co. KG	
Street:	Eisenbahnstraße 6-8	
Place:	D-68199 Mannheim	
Telephone:	+49 (621) 8504100	Telefax: +49 (621) 8504200
e-mail:	kundenservice@fdt.de	
Contact person:	Marco Anderer	Telephone: +49 (621) 8504563
e-mail:	marco.anderer@fdt.de	
Internet:	http://www.fdt.de	
Responsible Department:	Arbeitssicherheit und Umweltschutz	

1.4. Emergency telephone number:

Poison Control Center (Mayence, GER): +49 (0)6131 - 19240 (24h - de, en)
Emergency Action: In the event of a medical enquiry involving this product, please contact your doctor or local hospital accident and emergency department or the NHS enquiry service.

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No. 1272/2008

Hazard categories:

Flammable liquid: Flam. Liq. 2

Acute toxicity: Acute Tox. 4

Skin corrosion/irritation: Skin Irrit. 2

Serious eye damage/eye irritation: Eye Irrit. 2

Specific target organ toxicity - single exposure: STOT SE 3

Specific target organ toxicity - repeated exposure: STOT RE 1

Hazardous to the aquatic environment: Aquatic Acute 1

Hazardous to the aquatic environment: Aquatic Chronic 1

Hazard Statements:

Highly flammable liquid and vapour.

Harmful if inhaled.

Causes skin irritation.

Causes serious eye irritation.

May cause drowsiness or dizziness.

Causes damage to organs through prolonged or repeated exposure.

Very toxic to aquatic life.

Very toxic to aquatic life with long lasting effects.

2.2. Label elements

Regulation (EC) No. 1272/2008

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Rhepanol-Dachfarbe Kupfer

Revision date: 02.03.2018

Product code: RCSO-FDT-041

Page 2 of 12

Hazard components for labelling

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane
Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclenes, aromatics (2-25%)
copper flakes (coated with aliphatic acid)

Signal word: Danger

Pictograms:



Hazard statements

H225 Highly flammable liquid and vapour.
H315 Causes skin irritation.
H319 Causes serious eye irritation.
H332 Harmful if inhaled.
H336 May cause drowsiness or dizziness.
H372 Causes damage to organs through prolonged or repeated exposure.
H410 Very toxic to aquatic life with long lasting effects.

Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P243 Take action to prevent static discharges.
P260 Do not breathe dust/fume/gas/mist/vapours/spray.
P391 Collect spillage.
P280 Wear protective gloves/protective clothing/eye protection/face protection.
P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/doctor.
P302+P352 IF ON SKIN: Wash with plenty of water.
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P331 Do NOT induce vomiting.
P332+P313 If skin irritation occurs: Get medical advice/attention.
P337+P313 If eye irritation persists: Get medical advice/attention.
P501 Dispose of contents/container in accordance with national disposal regulations.

2.3. Other hazards

In use, may form flammable/explosive vapour-air mixture.
The components in this mixture do not meet the criteria for classification as PBT or vPvB.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Rhepanol-Dachfarbe Kupfer

Revision date: 02.03.2018

Product code: RCSO-FDT-041

Page 3 of 12

Hazardous components

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification according to Regulation (EC) No. 1272/2008 [CLP]			
	Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane			40-60 %
	921-024-6		01-2119475514-35	
	Flam. Liq. 2, Skin Irrit. 2, STOT SE 3, Asp. Tox. 1, Aquatic Chronic 2; H225 H315 H336 H304 H411			
	Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclenes, aromatics (2-25%)			30-50 %
	927-344-2		01-2119463586-28	
	Flam. Liq. 3, STOT SE 3, STOT RE 1, Asp. Tox. 1, Aquatic Chronic 2; H226 H336 H372 H304 H411			
-	copper flakes (coated with aliphatic acid)			10-20 %
	-	029-019-01-X		
	Acute Tox. 3, Acute Tox. 4, Eye Irrit. 2, Aquatic Acute 1 (M-Factor = 10), Aquatic Chronic 1 (M-Factor = 10); H331 H302 H319 H400 H410			
64742-48-9	Naphtha (petroleum), hydrotreated heavy; Low boiling point hydrogen treated naphtha			1-<5 %
	265-150-3	649-327-00-6	01-2119457273-39	
	Asp. Tox. 1; H304			

Full text of H and EUH statements: see section 16.

Further Information

There is the following note: The classification of "Hydrocarbons, C8-C10, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)" as a carcinogen or mutagen need not apply if it can be shown that the substance contains less than 0.1 wt% benzene (EINECS No 200-753-7). If the substance is not classified as a carcinogen, so at least the safety (102) -260-262-301 + 310-331 (Table 3.1) or the S phrases (2) -23-24-62 (Table 3.2) apply. This note applies only to certain complex oil-derived substances in Part 3 of this regulation.

There is the following note: The classification of "Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane" as a carcinogen or mutagen need not apply if it can be shown that the substance contains less than 0.1 wt% benzene (EINECS No 200-753-7). If the substance is not classified as a carcinogen, so at least the safety (102) -260-262-301 + 310-331 (Table 3.1) or the S phrases (2) -23-24-62 (Table 3.2) apply. This note applies only to certain complex oil-derived substances in Part 3 of this regulation.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

In case of troubles or persistent symptoms, consult an doctor/physician.

Remove persons from danger area and lie them down. Never orally infuse something to an unconscious person. No special first aid measures necessary. A vomiting, supine person must be brought into recovery position.

After inhalation

Provide fresh air. In case of respiratory tract irritation, consult a physician.

In case of irregular breathing or respiratory arrest, perform artificial respiration.

After contact with skin

After contact with skin, wash immediately with plenty of water and soap. Change contaminated clothing. In case of skin irritation, consult a physician.

After contact with eyes

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Rhepanol-Dachfarbe Kupfer

Revision date: 02.03.2018

Product code: RCSO-FDT-041

Page 4 of 12

After ingestion

Rinse mouth, spit liquid again. Do NOT induce vomiting. Let water be drunken in little sips (dilution effect). Call a physician immediately. Do NOT induce vomiting. Aspiration hazard.

4.2. Most important symptoms and effects, both acute and delayed

Following inhalation: May cause drowsiness or dizziness.

After skin contact: Causes skin irritation.

In case of ingestion: If the material gets into the lungs, the following signs and symptoms may occur: tussive irritation, gasping, wheezing, dyspnea, respiratory tract blocked by mucus, short breath and/or fever.

Impairment of the respiratory organs may also occur after a few hours after the exposure.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Carbon dioxide (CO₂). Extinguishing powder. Water spray. Fight larger fires with water spray jet or alcohol-resistant foam.

Unsuitable extinguishing media

High power water jet.

5.2. Special hazards arising from the substance or mixture

Vapours may form explosive mixtures with air. Vapours are heavier than air and will spread at floor level.

Thermal decomposition can lead to harmful gases and vapours.

5.3. Advice for firefighters

Co-ordinate fire-fighting measures to the fire surroundings. Wear a self-contained breathing apparatus and chemical protective clothing.

Additional information

Do not allow to enter into surface water or drains.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Provide adequate ventilation. Keep away from sources of ignition - No smoking.

Avoid contact with skin, eyes and clothes. Wear personal protection equipment.

6.2. Environmental precautions

Do not allow to enter into surface water or drains.

In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

6.3. Methods and material for containment and cleaning up

Take up mechanically. Treat the recovered material as prescribed in the section on waste disposal.

6.4. Reference to other sections

Safe handling: see section 7

Personal precautions: refer to section 8.

Disposal: see section 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Provide adequate ventilation as well as local exhaustion at critical locations. Handle and open container with care.

Advice on protection against fire and explosion

Keep away from sources of ignition - No smoking. Take precautionary measures against static discharges.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Rhepanol-Dachfarbe Kupfer

Revision date: 02.03.2018

Product code: RCSO-FDT-041

Page 5 of 12

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Store only in original container. Keep container tightly closed in a cool, well-ventilated place.

7.3. Specific end use(s)

coating

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

DNEL/DMEL values

CAS No	Substance			
DNEL type	Exposure route	Effect	Value	
	Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane			
Worker DNEL, long-term	dermal		300 mg/kg bw/day	
Worker DNEL, long-term	inhalation		2085 mg/m ³	
Consumer DNEL, long-term	oral		149 mg/kg bw/day	
Consumer DNEL, long-term	dermal		149 mg/kg bw/day	
Consumer DNEL, long-term	inhalation		447 mg/m ³	

8.2. Exposure controls

Protective and hygiene measures

Change contaminated clothing. Wash hands before breaks and after work. When using do not eat or drink.

Avoid skin, eye and clothing contact. After contact with skin, wash immediately with plenty of water and soap or a suitable cleaning agent.

Eye/face protection

Tightly fitting safety glasses with side shields.

Hand protection

Protect skin by using skin protective cream. Wear suitable gloves.

When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits.

The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances.

NBR (Nitrile rubber).

Skin protection

Full cover clothing covering arms and legs.

Respiratory protection

Use protective filter mask in case of short-term and low exposure; in case of intense or longer exposure, use respiratory protection device operating independently from circulating air.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state: viscous
 Colour: according to product description
 Odour: like gasoline

pH-Value: not determined

Changes in the physical state

Melting point: not determined

Test method

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Rhepanol-Dachfarbe Kupfer

Revision date: 02.03.2018

Product code: RCSO-FDT-041

Page 6 of 12

Initial boiling point and boiling range: 80 °C

Flash point: -11 °C

Flammability

Gas: not determined

Explosive properties

The product is not explosive, however, formation of explosive mixtures are possible.

Lower explosion limits: 0,6 vol. %

Upper explosion limits: 6,5 vol. %

Ignition temperature: 270 °C

Auto-ignition temperature

Gas: not determined

Decomposition temperature: not determined

Oxidizing properties

not determined

Vapour pressure:
(at 20 °C) 21 hPaDensity (at 20 °C): 0,9 g/cm³

Water solubility: insoluble

Partition coefficient: not determined

Viscosity / dynamic:
(at 20 °C) 2500-6000 mPa·s ISO 2555

Viscosity / kinematic: not determined

Vapour density: not determined

Solvent content: 80-90 %

9.2. Other information

No further information available.

SECTION 10: Stability and reactivity**10.1. Reactivity**

No dangerous reactivity under regular conditions.

10.2. Chemical stability

The product is stable under regular conditions.

10.3. Possibility of hazardous reactions

No known hazardous reactions.

10.4. Conditions to avoid

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

10.5. Incompatible materials

Oxidizing agents, strong.

10.6. Hazardous decomposition products

Thermal decomposition can lead to harmful gases and vapours.

SECTION 11: Toxicological information**11.1. Information on toxicological effects****Acute toxicity**

Based on available data, the classification criteria are not met.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Rhepanol-Dachfarbe Kupfer

Revision date: 02.03.2018

Product code: RCSO-FDT-041

Page 7 of 12

ATEmix calculated

ATE (inhalative aerosol) 3,551 mg/l

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
	Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane				
	oral	LD50 >5000 mg/kg	Rat		
	dermal	LD50 >1999 mg/kg	Rabbit		
	inhalative (4 h) vapour	LC50 >23,2 mg/l	Rat		
	Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclenes, aromatics (2-25%)				
	oral	LD50 15000 mg/kg	Rat		OECD 401
	dermal	LD50 3400 mg/kg	Rabbit		OECD 402
-	copper flakes (coated with aliphatic acid)				
	oral	ATE 500 mg/kg			
	inhalative vapour	ATE 3 mg/l			
	inhalative aerosol	ATE 0,5 mg/l			

Irritation and corrosivity

Irritating to skin.

Sensitising effects

Based on available data, the classification criteria are not met.

Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

STOT-single exposure

Vapours may cause drowsiness and dizziness. (Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane)

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

12.1. Toxicity

Toxic to aquatic life with long lasting effects.

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h] [d]	Species	Source	Method
	Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane					
	Acute fish toxicity	LC50 >1-<=10 mg/l	96 h			
	Acute crustacea toxicity	EC50 >1-<=10 mg/l	48 h			

12.2. Persistence and degradability

No data available.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Rhepanol-Dachfarbe Kupfer

Revision date: 02.03.2018

Product code: RCSO-FDT-041

Page 8 of 12

CAS No	Chemical name			
	Method	Value	d	Source
	Evaluation			
	Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclenes, aromatics (2-25%)			
	Easily biodegradable (concerning to the criteria of the OECD).	74,4 %	28	
	Easily biodegradable (concerning to the criteria of the OECD).			

12.3. Bioaccumulative potential

No data available.

12.4. Mobility in soil

No data available.

12.5. Results of PBT and vPvB assessment

The components in this mixture do not meet the criteria for classification as PBT or vPvB.

12.6. Other adverse effects

No data available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Advice on disposal

Disposal according to official regulations.

Consult the local waste disposal expert about waste disposal. According to EAKV, allocation of waste identity numbers/waste descriptions must be carried out in a specific way for every industry and process.

Waste disposal number of waste from residues/unused products

080111 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU and removal of paint and varnish; waste paint and varnish containing organic solvents or other hazardous substances; hazardous waste

Waste disposal number of contaminated packaging

150110 WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED; packaging (including separately collected municipal packaging waste); packaging containing residues of or contaminated by hazardous substances; hazardous waste

Contaminated packaging

Non-contaminated packages may be recycled. Handle contaminated packages in the same way as the substance itself.

SECTION 14: Transport information

Land transport (ADR/RID)

14.1. UN number: UN 1263

14.2. UN proper shipping name: Paint

14.3. Transport hazard class(es): 3

14.4. Packing group: II

Hazard label: 3



Classification code: F1

Special Provisions: 163 367 640D 650

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Rhepanol-Dachfarbe Kupfer

Revision date: 02.03.2018

Product code: RCSO-FDT-041

Page 9 of 12

Limited quantity: 5 L
 Excepted quantity: E2
 Transport category: 2
 Hazard No: 33
 Tunnel restriction code: D/E

Inland waterways transport (ADN)

14.1. UN number: UN 1263
14.2. UN proper shipping name: Paint
14.3. Transport hazard class(es): 3
14.4. Packing group: II
 Hazard label: 3



Classification code: F1
 Special Provisions: 163 367 640D 650
 Limited quantity: 5 L
 Excepted quantity: E2

Marine transport (IMDG)

14.1. UN number: UN 1263
14.2. UN proper shipping name: Paint
14.3. Transport hazard class(es): 3
14.4. Packing group: II
 Hazard label: 3



Marine pollutant: Ja
 Special Provisions: 163, 367
 Limited quantity: 5 L
 Excepted quantity: E2
 EmS: F-E, S-E

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number: UN 1263
14.2. UN proper shipping name: Paint
14.3. Transport hazard class(es): 3
14.4. Packing group: II
 Hazard label: 3



Special Provisions: A3 A72 A192
 Limited quantity Passenger: 1 L
 Passenger LQ: Y341
 Excepted quantity: E2
 IATA-packing instructions - Passenger: 353
 IATA-max. quantity - Passenger: 5 L
 IATA-packing instructions - Cargo: 364

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Rhepanol-Dachfarbe Kupfer

Revision date: 02.03.2018

Product code: RCSO-FDT-041

Page 10 of 12

IATA-max. quantity - Cargo:

60 L

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: yes



14.6. Special precautions for user

No special precautions known.

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

Additional information

Regulation (EC) No. 1005/2009 on substances that lead to the depletion of the ozone layer: not applicable

Regulation (EC) No. 648/2004 (Detergents regulation): not applicable

Regulation (EC) No 850/2004 on persistent organic pollutants: not applicable

Regulation (EC) No 649/2012 of the European Parliament and of the Council concerning the export and import of dangerous chemicals: This mix contains no chemicals that are subject to the export notification procedures (annex 1).

This mixture contains the following substances of very high concern (SVHC) which are included in the Candidate List according to Article 59 of REACH: none

This mixture contains the following substances of very high concern (SVHC) which are subject to authorisation according to Annex XIV of REACH: none

National regulatory information

Water contaminating class (D): 2 - clearly water contaminating

15.2. Chemical safety assessment

For the following substances of this mixture a chemical safety assessment has been carried out:

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane

Naphtha (petroleum), hydrotreated heavy; Low boiling point hydrogen treated naphtha

SECTION 16: Other information

Changes

Version 1,00 - Creation - 02.03.2018

Abbreviations and acronyms

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

BImSchV (Fed.Imm.Prot.Act): Directive on the Implementation of the Federal Immission Protection Act

CAS: Chemical Abstracts Service

EC: Effective Concentration

EG: European Community (Europäische Gemeinschaft)

EN: European Norm

IATA: International Air Transport Association

IBC Code: International Code for the Construction and Equipment of ships carrying Dangerous Chemicals in Bulk

ICAO: International Civil Aviation Organization

IMDG: International Maritime Code for Dangerous Goods

CLP: Classification, Labeling, Packaging

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Rhepanol-Dachfarbe Kupfer

Revision date: 02.03.2018

Product code: RCSO-FDT-041

Page 11 of 12

IUCLID: International Uniform Chemical Information Database
 LC: Lethal concentration
 LD: Lethal dose
 log Kow: Octanol/water partition coefficient
 MARPOL: Maritime Pollution Convention = Convention for the Prevention of Maritime Pollution from Ships
 OECD: Organisation for Economic Co-operation and Development
 PBT: Persistent, bio-cumulative, toxic
 RID: Regulation Concerning the International Transport of Dangerous Goods by Rail
 TRGS: Technische Regeln für Gefahrstoffe
 VOC: Volatile Organic Compounds
 vPvB: very persistent and very bio-cumulative
 VwVwS: Administrative Regulation for Water Pollutants
 WGK: German Water Hazard Class
 GHS: Globally Harmonized System of Classification and Labelling of Chemicals
 EINECS: European Inventory of Existing Commercial Chemical Substances
 ELINCS: European List of Notified Chemical Substances
 DNEL: Derived No Effect Level
 PNEC: Predicted No Effect Concentration
 TLV: Threshold Limiting Value
 STOT: Specific Target Organ Toxicity

Classification for mixtures and used evaluation method according to Regulation (EC) No. 1272/2008 [CLP]

Classification	Classification procedure
Flam. Liq. 2; H225	Calculation method
Acute Tox. 4; H332	Calculation method
Skin Irrit. 2; H315	Calculation method
Eye Irrit. 2; H319	Calculation method
STOT SE 3; H336	Calculation method
STOT RE 1; H372	Calculation method
Aquatic Acute 1; H400	Calculation method
Aquatic Chronic 1; H410	Calculation method

Relevant H and EUH statements (number and full text)

H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H331	Toxic if inhaled.
H332	Harmful if inhaled.
H336	May cause drowsiness or dizziness.
H372	Causes damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.

Further Information

The information given in this safety data sheet is to describe the product's safety regulations. It is not for guaranteeing certain characteristics and is based on today's knowledge. The safety data sheet was generated upon information of pre-suppliers by:

REACHECK Solutions GmbH, Frohsinnstraße 28, 63739 Aschaffenburg, Germany
 Phone: +49 (0)6021 - 1 50 86-0, Fax: +49 (0)6021 - 1 50 86-77, E-Mail: eu-sds@reacheck.eu,
 www.reacheck.eu

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Rhepanol-Dachfarbe Kupfer

Revision date: 02.03.2018

Product code: RCSO-FDT-041

Page 12 of 12

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)