

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Primer 1 S

Print date: 16.12.2015

Product code: RCSO-FDT-008

Page 1 of 15

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Primer 1 S

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

priming

Uses advised against

Only use for the intended purpose.

The product is intended for professional use.

1.3. Details of the supplier of the safety data sheet

Company name:	FDT Flachdach Technologie GmbH & Co. KG	
Street:	Eisenbahnstraße 6-8	
Place:	D-68199 Mannheim	
Telephone:	+49 (621) 8504100	Telefax: +49 (621) 8504200
e-mail:	kundenservice@fdt.de	
Contact person:	Marco Anderer	Telephone: +49 (621) 8504563
e-mail:	marco.anderer@fdt.de	
Internet:	http://www.fdt.de	
Responsible Department:	Arbeitssicherheit und Umweltschutz	

1.4. Emergency telephone

Poison Control Center (Mayence, GER)

number: +49 (0)6131-19240 (24h - de, en)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No. 1272/2008

Hazard categories:

Flammable liquid: Flam. Liq. 2

Acute toxicity: Acute Tox. 4

Skin corrosion/irritation: Skin Irrit. 2

Serious eye damage/eye irritation: Eye Irrit. 2

Reproductive toxicity: Repr. 2

Specific target organ toxicity - repeated exposure: STOT RE 2

Hazardous to the aquatic environment: Aquatic Chronic 3

Hazard Statements:

Highly flammable liquid and vapour.

Causes serious eye irritation.

Causes skin irritation.

Suspected of damaging the unborn child.

May cause damage to organs through prolonged or repeated exposure.

Harmful to aquatic life with long lasting effects.

2.2. Label elements

Regulation (EC) No. 1272/2008

Hazard components for labelling

4-methylpentan-2-one, isobutyl methyl ketone

toluene

xylene

ethylbenzene

Signal word: Danger

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Primer 1 S

Print date: 16.12.2015

Product code: RCSO-FDT-008

Page 2 of 15

Pictograms:



Hazard statements

H225	Highly flammable liquid and vapour.
H319	Causes serious eye irritation.
H315	Causes skin irritation.
H361d	Suspected of damaging the unborn child.
H373	May cause damage to organs through prolonged or repeated exposure.
H412	Harmful to aquatic life with long lasting effects.

Precautionary statements

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P241	Use explosion-proof electrical/ventilating/lighting equipment.
P260	Do not breathe dust/fume/gas/mist/vapours/spray.
P303+P361+P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P308+P313	IF exposed or concerned: Get medical advice/attention.
P501	Dispose of contents/container in accordance with national disposal regulations.

2.3. Other hazards

The components in this mixture do not meet the criteria for classification as PBT or vPvB.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Primer 1 S

Print date: 16.12.2015

Product code: RCSO-FDT-008

Page 3 of 15

Hazardous components

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification according to Regulation (EC) No. 1272/2008 [CLP]			
108-10-1	4-methylpentan-2-one, isobutyl methyl ketone			10-<20 %
	203-550-1	606-004-00-4		
	Flam. Liq. 2, Acute Tox. 4, Eye Irrit. 2, STOT SE 3; H225 H332 H319 H335 EUH066			
1330-20-7	xylene			5-<15 %
	215-535-7	601-022-00-9		
	Flam. Liq. 3, Acute Tox. 4, Acute Tox. 4, Skin Irrit. 2; H226 H312 H332 H315			
108-88-3	toluene			5-<15 %
	203-625-9	601-021-00-3		
	Flam. Liq. 2, Repr. 2, Skin Irrit. 2, STOT SE 3, STOT RE 2, Asp. Tox. 1; H225 H361d H315 H336 H373 H304			
67-64-1	acetone; propan-2-one; propanone			1,0-<5 %
	200-662-2	606-001-00-8	01-2119471330-49	
	Flam. Liq. 2, Eye Irrit. 2, STOT SE 3; H225 H319 H336 EUH066			
100-41-4	ethylbenzene			1-<5 %
	202-849-4	601-023-00-4		
	Flam. Liq. 2, Acute Tox. 4, STOT RE 2, Asp. Tox. 1; H225 H332 H373 H304			
1314-13-2	zinc oxide			1,0-<1,5 %
	215-222-5	030-013-00-7		
	Aquatic Acute 1 (M-Factor = 1), Aquatic Chronic 1; H400 H410			
10584-98-2	2-ethylhexyl 4,4-dibutyl-10-ethyl-7-oxo-8-oxa-3,5-dithia-4-stannatetradecanoate			<0,2 %
	234-186-1			
	Muta. 2, Repr. 1A, Acute Tox. 4, Skin Irrit. 2, Eye Irrit. 2, STOT RE 1, Aquatic Acute 1, Aquatic Chronic 1; H341 H360 H302 H315 H319 H372 H400 H410			

Full text of H and EUH statements: see section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

In case of troubles or persistent symptoms, consult an doctor/physician.

Remove persons from danger area and lie them down. Never orally infuse something to an unconscious person. No special first aid measures necessary. A vomiting, supine person must be brought into recovery position.

After inhalation

Provide fresh air. In case of respiratory tract irritation, consult a physician.

In case of irregular breathing or respiratory arrest, perform artificial respiration.

After contact with skin

After contact with skin, wash immediately with plenty of water and soap. Change contaminated clothing. Call a physician immediately.

After contact with eyes

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Primer 1 S

Print date: 16.12.2015

Product code: RCSO-FDT-008

Page 4 of 15

After ingestion

Rinse mouth, spit liquid again. Do NOT induce vomiting. Let water be drunken in little sips (dilution effect). Call a physician immediately.

4.2. Most important symptoms and effects, both acute and delayed

After skin contact: Irritation and reddening.

Following eye contact: Causes serious eye irritation.

Possible risk of harm to the unborn child.

May cause damage to organs through prolonged or repeated exposure.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Carbon dioxide (CO₂). Sand. Extinguishing powder. Water spray. Fight larger fires with water spray jet or alcohol-resistant foam.

Unsuitable extinguishing media

High power water jet.

5.2. Special hazards arising from the substance or mixture

Thermal decomposition can lead to harmful gases and vapours.

5.3. Advice for firefighters

Co-ordinate fire-fighting measures to the fire surroundings. Wear a self-contained breathing apparatus and chemical protective clothing.

Additional information

Do not allow to enter into surface water or drains.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Provide adequate ventilation. Keep away from sources of ignition - No smoking.

Avoid contact with skin, eyes and clothes. Wear personal protection equipment.

6.2. Environmental precautions

Do not allow to enter into surface water or drains.

In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

6.3. Methods and material for containment and cleaning up

Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal. Provide adequate ventilation.

6.4. Reference to other sections

Safe handling: see section 7

Personal precautions: refer to section 8.

Disposal: see section 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Provide adequate ventilation as well as local exhaust at critical locations. Handle and open container with care.

Advice on protection against fire and explosion

Keep away from sources of ignition. - No smoking. Take precautionary measures against static discharges.

7.2. Conditions for safe storage, including any incompatibilities

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Primer 1 S

Print date: 16.12.2015

Product code: RCSO-FDT-008

Page 5 of 15

Requirements for storage rooms and vessels

Store only in original container. Keep container tightly closed in a cool, well-ventilated place.

7.3. Specific end use(s)

priming

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure limits (EH40)

CAS No	Substance	ppm	mg/m ³	fibres/ml	Category	Origin
108-10-1	4-Methylpentan-2-one	50	208		TWA (8 h)	WEL
		100	416		STEL (15 min)	WEL
67-64-1	Acetone	500	1210		TWA (8 h)	WEL
		1500	3620		STEL (15 min)	WEL
100-41-4	Ethylbenzene	100	441		TWA (8 h)	WEL
		125	552		STEL (15 min)	WEL
108-88-3	Toluene	50	191		TWA (8 h)	WEL
		100	384		STEL (15 min)	WEL
1330-20-7	Xylene: mixed isomers	50	220		TWA (8 h)	WEL
		100	441		STEL (15 min)	WEL

Biological Monitoring Guidance Values (EH40)

CAS No	Substance	Parameter	Value	Test material	Sampling time
108-10-1	4-methylpentan-2-one	4-methylpentan-2-one	20 µmol/L	urine	Post shift
1330-20-7	Xylene, o-, m-, p- or mixed isomers	methyl hippuric acid	650 mmol/mol	urine	Post shift

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Primer 1 S

Print date: 16.12.2015

Product code: RCSO-FDT-008

Page 6 of 15

DNEL/DMEL values

CAS No	Substance			
DNEL type		Exposure route	Effect	Value
108-10-1	4-methylpentan-2-one, isobutyl methyl ketone			
Consumer DNEL, long-term		oral		4,2 mg/kg bw/day
Consumer DNEL, long-term		dermal		4,2 mg/kg bw/day
Worker DNEL, long-term		dermal		11,8 mg/kg bw/day
Consumer DNEL, acute		inhalation		155,2 mg/m ³
Consumer DNEL, long-term		inhalation		14,7 mg/m ³
Worker DNEL, acute		inhalation		208 mg/m ³
Worker DNEL, long-term		inhalation		83 mg/m ³
108-88-3	toluene			
Consumer DNEL, long-term		oral		8,13 mg/kg bw/day
Consumer DNEL, long-term		dermal		226 mg/kg bw/day
Worker DNEL, long-term		dermal		384 mg/kg bw/day
Consumer DNEL, acute		inhalation		226 mg/m ³
Consumer DNEL, long-term		inhalation		56,5 mg/m ³
Worker DNEL, acute		inhalation		343 mg/m ³
Worker DNEL, long-term		inhalation		192 mg/m ³
67-64-1	acetone; propan-2-one; propanone			
Consumer DNEL, long-term		oral		62 mg/kg bw/day
Consumer DNEL, long-term		dermal		62 mg/kg bw/day
Worker DNEL, long-term		dermal		186 mg/kg bw/day
Consumer DNEL, long-term		inhalation		200 mg/m ³
Worker DNEL, acute		inhalation		2420 mg/m ³
Worker DNEL, long-term		inhalation		1210 mg/m ³
1314-13-2	zinc oxide			
Consumer DNEL, long-term		oral		0,83 mg/kg bw/day
Consumer DNEL, long-term		dermal		83,3 mg/kg bw/day
Worker DNEL, long-term		dermal		83,3 mg/kg bw/day
Consumer DNEL, long-term		inhalation		2,5 mg/m ³
Worker DNEL, long-term		inhalation		5 mg/m ³

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Primer 1 S

Print date: 16.12.2015

Product code: RCSO-FDT-008

Page 7 of 15

PNEC values

CAS No	Substance	
Environmental compartment		Value
108-10-1	4-methylpentan-2-one, isobutyl methyl ketone	
Freshwater		0,6 mg/l
Marine water		0,06 mg/l
Soil		1,3 mg/kg
Marine sediment		0,83 mg/kg
Freshwater sediment		8,27 mg/kg
Micro-organisms in sewage treatment plants (STP)		27,5 mg/l
108-88-3	toluene	
Freshwater		0,68 mg/l
Soil		2,89 mg/kg
Freshwater sediment		16,39 mg/kg
Micro-organisms in sewage treatment plants (STP)		13,61 mg/l
67-64-1	acetone; propan-2-one; propanone	
Freshwater		10,6 mg/l
Marine water		1,06 mg/l
Soil		29,5 mg/kg
Marine sediment		3,04 mg/kg
Freshwater sediment		30,4 mg/kg
Micro-organisms in sewage treatment plants (STP)		100 mg/l
1314-13-2	zinc oxide	
Freshwater		0,02 mg/l
Marine water		0,06 mg/l
Soil		35,6 mg/kg
Marine sediment		56,5 mg/kg
Freshwater sediment		117,8 mg/kg
Micro-organisms in sewage treatment plants (STP)		0,05 mg/l

8.2. Exposure controls

Protective and hygiene measures

Change contaminated clothing. Wash hands before breaks and after work. When using do not eat or drink.
Avoid skin, eye and clothing contact. After contact with skin, wash immediately with plenty of water and soap or a suitable cleaning agent.

Eye/face protection

Tightly fitting safety glasses with side shields.

Hand protection

Protect skin by using skin protective cream. Wear suitable gloves.
When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits.
The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances.

Suitable material: FKM (fluoro rubber)

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Primer 1 S

Print date: 16.12.2015

Product code: RCSO-FDT-008

Page 8 of 15

Skin protection

Full cover clothing covering arms and legs.

Respiratory protection

Use protective filter mask in case of short-term and low exposure; in case of intense or longer exposure, use respiratory protection device operating independently from circulating air.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state:	liquid
Colour:	blue
Odour:	characteristic

Test method

pH-Value:	not determined
-----------	----------------

Changes in the physical state

Melting point:	not determined
Initial boiling point and boiling range:	56 °C
Flash point:	-18 °C

Flammability

Gas:	not determined
------	----------------

Explosive properties

The product is not explosive, however, formation of explosive mixtures are possible.

Lower explosion limits:	1,1 vol. %
Upper explosion limits:	13,0 vol. %
Ignition temperature:	460 °C

Auto-ignition temperature

Gas:	not determined
------	----------------

Decomposition temperature:	not determined
----------------------------	----------------

Oxidizing properties

not determined

Vapour pressure: (at 20 °C)	247 hPa
--------------------------------	---------

Density (at 20 °C):	1,15 g/cm ³ ISO 2811
---------------------	---------------------------------

Water solubility:	insoluble
-------------------	-----------

Partition coefficient:	not determined
------------------------	----------------

Viscosity / dynamic: (at 20 °C)	240 mPa·s ISO 2555
------------------------------------	--------------------

Viscosity / kinematic:	not determined
------------------------	----------------

Vapour density:	not determined
-----------------	----------------

Solvent content:	not determined
------------------	----------------

9.2. Other information

Solid content:	not determined
----------------	----------------

No further information available.

SECTION 10: Stability and reactivity

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Primer 1 S

Print date: 16.12.2015

Product code: RCSO-FDT-008

Page 9 of 15

10.1. Reactivity

No dangerous reactivity under regular conditions.

10.2. Chemical stability

The product is stable under regular conditions.

10.3. Possibility of hazardous reactions

No known hazardous reactions.

10.4. Conditions to avoid

No information available.

10.5. Incompatible materials

No information available.

10.6. Hazardous decomposition products

Pyrolysis products, toxic. chlorine compounds.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity

Based on available data, the classification criteria are not met.

ATEmix calculated

ATE (inhalative aerosol) 3,761 mg/l

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Primer 1 S

Print date: 16.12.2015

Product code: RCSO-FDT-008

Page 10 of 15

CAS No	Chemical name				
	Exposure routes	Method	Dose	Species	Source
108-10-1	4-methylpentan-2-one, isobutyl methyl ketone				
	oral	LD50	2080 mg/kg	Rat	OECD 401
	dermal	LD50	>16000 mg/kg	Rabbit	
	inhalative (4 h) vapour	LC50	8,3-16,6 mg/l	Rat	OECD 403
	inhalative aerosol	ATE	1,5 mg/l		
1330-20-7	xylene				
	oral	LD50	4300 mg/kg	Rat	
	dermal	LD50	3200 mg/kg	Rabbit	
	inhalative (4 h) vapour	LC50	11 mg/l	Rat	
	inhalative aerosol	ATE	1,5 mg/l		
108-88-3	toluene				
	oral	LD50	>5000 mg/kg	Rat	
	dermal	LD50	>5000 mg/kg	Rabbit	
	inhalative (4 h) vapour	LC50	31 mg/l	Rat	
67-64-1	acetone; propan-2-one; propanone				
	oral	LD50	5800 mg/kg	Rat	OECD 401
	dermal	LD50	>15800 mg/kg	Rat	
	inhalative (4 h) vapour	LC50	76 mg/l	Rat	
100-41-4	ethylbenzene				
	oral	LD50	3500 mg/kg	Rat	GESTIS
	dermal	LD50	15400 mg/kg	Rabbit	GESTIS
	inhalative (4 h) vapour	LC50	17,2 mg/l	Rat	
	inhalative aerosol	ATE	1,5 mg/l		
1314-13-2	zinc oxide				
	oral	LD50	> 5000 mg/kg	Rat	
10584-98-2	2-ethylhexyl 4,4-dibutyl-10-ethyl-7-oxo-8-oxa-3,5-dithia-4-stannatetradecanoate				
	oral	ATE	500 mg/kg		

Irritation and corrosivity

Causes serious eye irritation.

Causes skin irritation.

Sensitising effects

Based on available data, the classification criteria are not met.

STOT-single exposure

Based on available data, the classification criteria are not met.

Severe effects after repeated or prolonged exposure

May cause damage to organs through prolonged or repeated exposure. (toluene), (ethylbenzene)

Carcinogenic/mutagenic/toxic effects for reproduction

Suspected of damaging the unborn child. (toluene)

Aspiration hazard

Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Primer 1 S

Print date: 16.12.2015

Product code: RCSO-FDT-008

Page 11 of 15

12.1. Toxicity

Harmful to aquatic life with long lasting effects.

CAS No	Chemical name					
	Aquatic toxicity	Method	Dose	[h] [d]	Species	Source
108-10-1	4-methylpentan-2-one, isobutyl methyl ketone					
	Acute fish toxicity	LC50	509 mg/l	96 h	Pimephales promelas	
	Acute algae toxicity	ErC50	400 mg/l	96 h	Selenastrum capricornutum	
	Acute crustacea toxicity	EC50	170 mg/l	48 h	Daphnia magna	
	Acute bacteria toxicity	(275 mg/l)			Pseudomonas putida	
1330-20-7	xylene					
	Acute fish toxicity	LC50	26,7 mg/l	96 h	Pimephales promelas (fathead minnow)	
	Acute algae toxicity	ErC50	2,2 mg/l	72 h		
	Acute crustacea toxicity	EC50	1 mg/l	48 h	Daphnia magna (Big water flea)	
108-88-3	toluene					
	Acute fish toxicity	LC50	24 mg/l	96 h	Onchorhynchus mykiss (Rainbow trout)	
	Acute algae toxicity	ErC50	12 mg/l	72 h	Pseudokirchneriella subcapitata	
	Acute crustacea toxicity	EC50	11,5 mg/l	48 h	Daphnia magna	
	Acute bacteria toxicity	(29 mg/l)			Pseudomonas putida	
67-64-1	acetone; propan-2-one; propanone					
	Acute fish toxicity	LC50	5540 mg/l	96 h	Onchorhynchus mykiss	
	Acute crustacea toxicity	EC50	6100 mg/l	48 h	Daphnia magna	
	Algae toxicity	NOEC	4740 mg/l	2 d	Selenastrum capricornutum	
100-41-4	ethylbenzene					
	Acute algae toxicity	ErC50	3,6 mg/l	96 h		GESTIS
1314-13-2	zinc oxide					
	Acute fish toxicity	LC50	1,31 mg/l	96 h	Onchorhynchus mykiss (Rainbow trout)	
	Acute algae toxicity	ErC50	0,21 mg/l	72 h	Pseudokirchneriella subcapitata	
	Acute crustacea toxicity	EC50	2,2 mg/l	48 h	Daphnia magna	
	Algae toxicity	NOEC	0,04 mg/l		Pseudokirchneriella subcapitata	

12.2. Persistence and degradability

No data available.

12.3. Bioaccumulative potential

No data available.

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
108-10-1	4-methylpentan-2-one, isobutyl methyl ketone	1,31
108-88-3	toluene	2,73
67-64-1	acetone; propan-2-one; propanone	-0,24
100-41-4	ethylbenzene	3,15

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Primer 1 S

Print date: 16.12.2015

Product code: RCSO-FDT-008

Page 12 of 15

12.4. Mobility in soil

No data available.

12.5. Results of PBT and vPvB assessment

The components in this mixture do not meet the criteria for classification as PBT or vPvB.

12.6. Other adverse effects

No data available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Advice on disposal

Disposal according to official regulations.

Consult the local waste disposal expert about waste disposal. According to EAKV, allocation of waste identity numbers/waste descriptions must be carried out in a specific way for every industry and process.

Waste disposal number of waste from residues/unused products

080111 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU and removal of paint and varnish; waste paint and varnish containing organic solvents or other hazardous substances
Classified as hazardous waste.

Waste disposal number of contaminated packaging

150110 WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED; packaging (including separately collected municipal packaging waste); packaging containing residues of or contaminated by hazardous substances
Classified as hazardous waste.

Contaminated packaging

Non-contaminated packages may be recycled. Handle contaminated packages in the same way as the substance itself.

SECTION 14: Transport information

Land transport (ADR/RID)

14.1. UN number: UN 1263

14.2. UN proper shipping name: Paint

14.3. Transport hazard class(es): 3

14.4. Packing group: II

Hazard label: 3



Classification code: F1
Special Provisions: 163 640D 650
Limited quantity: 5 L
Excepted quantity: E2
Transport category: 2
Hazard No: 33
Tunnel restriction code: D/E

Inland waterways transport (ADN)

14.1. UN number: UN 1263

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Primer 1 S

Print date: 16.12.2015

Product code: RCSO-FDT-008

Page 13 of 15

14.2. UN proper shipping name: Paint

14.3. Transport hazard class(es): 3

14.4. Packing group: II

Hazard label: 3



Classification code: F1

Special Provisions: 163 640D 650

Limited quantity: 5 L

Excepted quantity: E2

Marine transport (IMDG)

14.1. UN number: UN 1263

14.2. UN proper shipping name: Paint

14.3. Transport hazard class(es): 3

14.4. Packing group: II

Hazard label: 3



Marine pollutant: Nein

Special Provisions: 163

Limited quantity: 5 L

Excepted quantity: E2

EmS: F-E, S-E

Air transport (ICAO)

14.1. UN number: UN 1263

14.2. UN proper shipping name: Paint

14.3. Transport hazard class(es): 3

14.4. Packing group: II

Hazard label: 3



Special Provisions: A3 A72

Limited quantity Passenger: 1 L

Passenger LQ: Y341

Excepted quantity: E2

IATA-packing instructions - Passenger: 353

IATA-max. quantity - Passenger: 5 L

IATA-packing instructions - Cargo: 364

IATA-max. quantity - Cargo: 60 L

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: no

14.6. Special precautions for user

No special precautions known.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Primer 1 S

Print date: 16.12.2015

Product code: RCSO-FDT-008

Page 14 of 15

14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

not applicable

SECTION 15: Regulatory information**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture****EU regulatory information**

2004/42/EC (VOC): 51,59%

Additional information

Regulation (EC) No. 1005/2009 on substances that lead to the depletion of the ozone layer: not applicable

Regulation (EC) No. 648/2004 (Detergents regulation): not applicable

REGULATION (EC) No 850/2004 on persistent organic pollutants: not applicable

REGULATION (EC) No 689/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL concerning the export and import of dangerous chemicals: This mix contains no chemicals that are subject to the export notification procedures (annex 1).

This mixture contains the following substances of very high concern (SVHC) which are included in the Candidate List according to Article 59 of REACH: none

This mixture contains the following substances of very high concern (SVHC) which are subject to authorisation according to Annex XIV of REACH: none

National regulatory information

Water contaminating class (D): 2 - water contaminating

15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information**Changes**

Version 1,00 - Creation - 26.01.2012

Version 1,01 - Classification/Labeling according Regulation No.1272/2008 (GHS/CLP) and general revision - 24.06.2015

Abbreviations and acronyms

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

BlmSchV (Fed.Imm.Prot.Act): Directive on the Implementation of the Federal Immission Protection Act

CAS: Chemical Abstracts Service

EC: Effective Concentration

EG: European Community (Europäische Gemeinschaft)

EN: European Norm

IATA: International Air Transport Association

IBC Code: International Code for the Construction and Equipment of ships carrying Dangerous Chemicals in Bulk

ICAO: International Civil Aviation Organization

IMDG: International Maritime Code for Dangerous Goods

CLP: Classification, Labeling, Packaging

IUCLID: International Uniform Chemical Information Database

LC: Lethal concentration

LD: Lethal dose

log Kow: Octanol/water partition coefficient

MARPOL: Maritime Pollution Convention = Convention for the Prevention of Maritime Pollution from Ships

OECD: Organisation for Economic Co-operation and Development

PBT: Persistent, bio-cumulative, toxic

RID: Regulation Concerning the International Transport of Dangerous Goods by Rail

TRGS: Technische Regeln für Gefahrstoffe

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Primer 1 S

Print date: 16.12.2015

Product code: RCSO-FDT-008

Page 15 of 15

VOC: Volatile Organic Compounds
vPvB: very persistent and very bio-cumulative
VwVwS: Administrative Regulation for Water Pollutants
WGK: German Water Hazard Class
GHS: Globally Harmonized System of Classification and Labelling of Chemicals
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
DNEL: Derived No Effect Level
PNEC: Predicted No Effect Concentration
TLV: Threshold Limiting Value
STOT: Specific Target Organ Toxicity

Relevant H and EUH statements (number and full text)

H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H341	Suspected of causing genetic defects.
H360	May damage fertility or the unborn child.
H361d	Suspected of damaging the unborn child.
H372	Causes damage to organs through prolonged or repeated exposure.
H373	May cause damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
EUH066	Repeated exposure may cause skin dryness or cracking.

Further Information

The information given in this safety data sheet is to describe the product's safety regulations. It is not for guaranteeing certain characteristics and is based on today's knowledge. The safety data sheet was generated upon information of pre-suppliers by:

REACHECK Solutions GmbH, Frohsinnstraße 28, 63739 Aschaffenburg, Germany
Phone: +49 (0)6021 - 1 50 86-0, Fax: +49 (0)6021 - 1 50 86-77, E-Mail: eu-sds@reackcheck.eu,
www.reackcheck.eu

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)