

A solid foundation for green roofs.



Rhepanol® hg



He who sows on Rhepanol® hg, will reap enormous benefits.



In the spirit of Feng Shui: Rhepanol hg on the shopping centre “Life” in Munich.

**Discover the “green”
version of a successful
roofing membrane
system: Rhepanol hg**

Actually, there should be no need to introduce Rhepanol. This name speaks for itself. The total number of square metres of this membrane installed on top of the most different buildings worldwide is simply overwhelming. Figures amount to over 95 million square metres of Rhepanol fk. But have you also heard of **Rhepanol hg**? This membrane is far more than just another good reason to rely on the know-how and the established quality of FDT when waterproofing flat roofs. Rhepanol hg is the perfect solution for every kind of “green” roof – intensive or extensive, or landscaped, to your own demands. Whether for new buildings or refurbishment projects.

**Specially designed for ever
growing demands**

What is so special about **Rhepanol hg**? Well it is designed to meet the criteria laid out in the FLL Guideline for resistance to root penetration. As to its ingredients, this roofing membrane is also based on the long-term proven material polyisobutylene (PIB), as has already been the case with **Rhepanol fk** for 30 years. The difference, however, why progressing and even persistently boring root systems will despair of **Rhepanol hg**, lies elsewhere. **Rhepanol hg** is optimised in terms of resistance to root penetration and hot air welding characteristics. That is why the seams are also absolutely resistant to root penetration without any further sealing. And this is exactly what the “h” stands for in the name. The “g” means the stabilisation of the roofing membrane by the central glass fleece reinforcement.



Rhepanol hg
*Roof sealing and root penetration
protection in one single membrane.*

QUICK-CHECK

- Based on PIB (polyisobutylene)
- Root resistant according to the FLL Guideline
- Hot air weldable
- Dimensionally stable due to the glass fleece reinforcement
- For intensive, extensive and landscaped green roofs
- Ideal for new buildings – and perfect for roof refurbishment, because of its compatibility with bitumen
- Membrane width: 2.05 m
- Colour: grey

Meadow idyll on the roof top thanks to Rhepanol® hg – the shopping centre Meydan in Istanbul.



SHOPPING CENTRE MEYDAN, ISTANBUL

- Built in 2007
- Principal: Metro Group Asset Management
- Architects: Foreign Office Architects (FOA), London
- System: Rhepanol hg
- Loosely laid layer build-up under ballast with vegetation
- Total roof area: 31,000 sqm
- Thereof with extensive vegetation: 28,000 sqm
- With intensive vegetation: 1,000 sqm



In Turkish, “Meydan” means “market place” or “place for encounters”. The green roofs spanning the square, however, are also accessible and alive. The shopping centre features a unique roof landscape with folds and smooth transitions.

What is a green roof to expect from Rhepanol® hg? A long and carefree life.



Pure harmony: Rhepanol hg protects the "Penny" supermarket in the town of Werne an der Lippe, Germany

Meeting the demands for green roofs with Rhepanol hg

With **Rhepanol hg**, designers, landscape architects and installers find even more benefits from the **Rhepanol** quality mark. This solution meets the demands of our times. Principals, investors and house owners are ever more eager to have green roof areas. Along with aesthetic and ecological advantages, a green roof is a convincing alternative in particular with respect to economic aspects. So it is no longer a secret, but rather common understanding that planted roof coverings have a significantly longer service life due to the protection against UV radiation, temperature extremes, hailstorms and encrustation.



Easy application of Rhepanol hg by hot air welding, without any further sealing.

Use the root resistance of Rhepanol hg Systematically

Rhepanol hg forms the basis for a long-term irreproachable maintenance of the roof area. The arithmetics are simple: the high longevity which is characteristic for all **Rhepanol** products anyway, plus the root resistance of **Rhepanol hg**, plus the life extending properties of a professionally installed vegetation layer, will make customer satisfaction a timeless feature. And just as plausible as this flat roof mathematics is the constantly high quality of **Rhepanol hg**, which is in particular underlined by these two certificates.

Considering the experts recommendations

No. 1: The General Building Construction Supervision Test Certificate of the State Material Testing Institute (MPA) Darmstadt.

No. 2: Certificate of the C.A.U. GmbH for an outstanding ecological profile according to DIN EN ISO 14040 ff. within a life cycle assessment.





Rhepanol hg used as a base for an extensive green roof.

Rhepanol hg keeps roots, rhizomes and co. at a distance

With **Rhepanol hg** as a sealing under the vegetation ballast, the space for development of the flora is clearly limited. Where the roofing membrane ends, i.e. at the upper edge, as far as the vegetation is concerned the protection against root penetration starts. This means "So far and no further!". For extensive vegetation like moss sedum, or grass herb variations, as well as for vegetation mats of plants needing more care like lawns, perennials, bushes, shrubs or even trees. **Rhepanol hg** will not surrender.

Even more: Rhepanol hg incorporates the best qualities

This positive "repelling behaviour" of **Rhepanol hg** does not lose its effectiveness even in contact with water. The hot air welded seam area is 100 % watertight. The fact that the roofing membrane remains unaffected by external influences, is due to its robust constitution. It is sustained, for example, by a balanced ratio of tensile strength and elongation. Owing to the high flexibility the covering and the seams are almost free from tensions. A similar advantage is provided by the very good perforation resistance, providing protection against impact loads, in particular during the application. All this, in combination with flexibility at extremely low temperature and the resistance to UV-radiation and hailstorms, results in outstanding performance.

QUICK-CHECK

- Loose laying with vegetation as ballast
- Outstanding ecological profile: free from plasticizers, halogen fire proofing agents and heavy metals
- Highly resistant to perforation
- Flexible temperatures down to -60 °C
- Hail-resistant according to DIN EN 13583
- Permanently resistant to UV-radiation
- Compatible with all kinds of insulation materials and resistant to polystyrene
- No fire hazard from open flames
- Compatible for application with Rhepanol fk and self-sealing edge

Rhepanol® hg. Complete protection against root penetration.



No understatement – with Rhepanol hg the only growth is – upward.

Rhepanol hg – the only base to build on! Simple and reliable.

The layer build-up may vary for different green roofs. Most preferably, however, **Rhepanol hg** should be an integral part of it. Just as you can see in the photo on the right. As a first layer on the supporting deck, the FDT vapour control layer. The next layer provides the thermal insulation (e.g. PU or PIR). Due to the compatibility of **Rhepanol hg** with most forms of insulation, the roofing membrane can be rolled out directly onto it – without a separation layer. Next, the drainage layer is installed for the protection, the storing and draining of water. The last but one layer is a rot-proof synthetic fleece serving as a filter and preventing substrate particles from soiling the drainage layer. On top of the layer build-up you will have the vegetation substrate with the plants growing on it.

Seamlessly watertight:

Rhepanol hg provides reliable protection against root penetration!

In practice, when unrolling the membrane the edges overlap by five centimetres. The membrane seams are heated with a handheld hot air welder or a welding machine and homogeneously fused together with a pressure roller. The glass fleece reinforcement sustains the shape and consistency of the material throughout the welding process. The effect is most desirable: The membranes melt into an inseparable connection which withstands any intrusion.

Also easily integrated:

Rhepanol hg with Rhepanol

In the situation that the design concept means a combination of planted and exposed, or “nongreen” roof areas, on the same building, a combination of both forms of the **Rhepanol** system is no problem! There is even no need for constructional separation in the connecting areas.

Loosely laid with ballast.



The layers from the top to the bottom:

- Vegetation
- Vegetation substrate
- Filter layer
- Drainage layer
- **Rhepanol hg**
- Thermal insulation layer
- FDT vapour control layer fk

Hot air welded.



**FDT Flachdach
Technologie GmbH**

Eisenbahnstraße 6–8
68199 Mannheim, Germany

Tel +49 6 21-85 04-0
Fax +49 6 21-85 04-2 00
www.fdt.de

Kundensupport:

Tel +49 6 21-85 04-1 00

Fax +49 6 21-85 04-2 00

E-Mail kundensupport@fdt.de