

Technical Information Sheet



FDT Activator (for adhesive and sealing compound)

Delivery form	Item Number
1.000 ml aluminum bottle	14 90 010

Description

The FDT Activator is a colorless, solvent-based surface activator that, due to its special settings, is particularly suitable as a cleaning and activation agent.

Scope of application

The FDT Activator is used to clean and activate the contact surfaces when laying FDT paving tiles (Rhepanol h paving tiles and Rhenofol paving tiles) with the FDT Adhesive and Sealant Compound.

Notes on processing

The FDT Activator is preferably applied with protective gloves (Art. No. 1750040) and cleaning tissues (Art. No. 1750050) onto the bonding surfaces of the FDT roofing membranes and FDT paving tiles with light pressure and wiped off. At least two wiping processes are required. The cleaning tissues must be changed after each wiping process. Leave it to air thoroughly afterwards. The product contains isopropanol.

Consumption

Approx. 10 ml/m

Properties

Technical data	Declared value
Color	colorless
Base	solvent-based bonding agent
Density	0.80 g/cm ³
Flash-off time at +20 °C/50 % relative humidity	approx. 10 min.
Application temperature	optimal at + 5 °C to + 30 °C

Storage

Optimal at + 15 °C to + 25 °C

Shelf life

Minimum 1 year at room temperature in unopened original container.

Packaging and disposal

1,000 ml aluminum bottle.

Refer to Safety Data Sheets (SDS) for more information.

Waste code number: 140603 (see section 13 safety data sheet)

Cleaning

Immediately wipe off splashes and soiling caused by the FDT Activator with a clean, non-linting and non-staining tissue made of cellulose or cotton (cleaning tissues item no. 1750050).

Precautions and occupational safety

See safety data sheet.

Transport

Information on transport labeling can be found in section 14 of the safety data sheet.

Note: As our products are constantly evolving, please contact our technical department or visit www.fdt.de for the latest information on our products.

Legal Notice:

We refer emphatically to the fact, that all details mentioned, especially the application and utilization recommendation for the products and their system accessories, have been developed under normal conditions, and based on our knowledge and experience. Appropriate storage and usage of the products are assumed. A warranty or reliability of a finished project cannot be deduced because of varying materials, substrates and differing work conditions, neither by any indications nor from verbal statements, irrespective of any legal positions. For the possible accusation that FDT acted intentionally or grossly negligent, the user has to supply evidence that they provided FDT with all information and details necessary for an appropriate and correct evaluation through FDT in written form, immediately available and complete. The user is responsible for ensuring that the products are suitable for the given application. It is FDT's right to change product specifications without notice. Property rights of third parties are to be considered. In addition, our particular sales and delivery terms are valid. The latest version of our product data sheet is obligatory, which can be requested directly through FDT. All information as well as all technical and drawing data comply with current technical standards and are based on our experience. National standards and regulations must be observed.

Technical changes reserved. As of 5th January 2026 | © 2026 FDT Flachdach Technologie GmbH, Mannheim, Germany