

Technical Information Sheet



FDT kick protection profile 200 one-piece

Delivery form	Item Number
1 piece of kick protection profile 200; 3.00 m x 0.20 m	14 08 100

Description

The kick protection profile 200 is a rigid, 3 m long, 200 mm high and 1.5 mm thick perforated aluminium rail. Untreated execution with foil. Holes with a diameter of 7 mm have been pre-drilled at 150 mm intervals for fixing the profile.

Application and processing

The kick protection profile 200 is designed for fixing and protecting roofing membranes on vertical elements in terraces and balconies. It prevents mechanical damage, for example in the edge area of the slab covering to the waterproofing membrane.

Mounting: Up to 5 fixings per meter are possible.

Properties

Technical data	Declared value
Material	Aluminium
Material thickness	1.5 mm
Front panel height	200 mm
Length	3,000 mm
System Components	Kick plate profile, connector
Holes	Starting at 100 mm, a 7-mm round hole every 200 mm
Packaging	6 m: 2 pieces, including 1 connector; or 15 m: 5 pieces, including 4 connectors
Standard Accessories	Connectors, 90-degree inside/outside corners



Optional orderable accessories:

FDT inside corner for kick protection profile 200

For execution of a 90° inside corner. Untreated execution with foil.

Color	Packaging unit	Item number
untreated aluminum	1 piece	14 08 110



FDT outside corner for kick protection profile

For execution of a 90° outside corner. Untreated execution with foil.

Color	Packaging unit	Item number
untreated aluminum	1 piece	14 08 120



FDT connector kick protection profile 200

Color	Packaging unit	Item number
untreated aluminum	1 piece	14 08 130



Storage

Keep dry in its original packaging.

Shelf life

Unlimited, provided it is stored correctly.

Packaging and disposal

Disposal codes/waste number: 17 04 02 (natural aluminium)

Precautions and occupational safety

General safety regulations must be observed.

Transport

General safety regulations must be observed.

Please note: As our products are constantly evolving, please contact our technical department or visit www.fdt.de for the latest information on our products.

Legal Notice:

We refer emphatically to the fact, that all details mentioned, especially the application and utilization recommendation for the products and their system accessories, have been developed under normal conditions, and based on our knowledge and experience. Appropriate storage and usage of the products are assumed. A warranty or reliability of a finished project cannot be deduced because of varying materials, substrates and differing work conditions, neither by any indications nor from verbal statements, irrespective of any legal positions. For the possible accusation that FDT acted intentionally or grossly negligent, the user has to supply evidence that they provided FDT with all information and details necessary for an appropriate and correct evaluation through FDT in written form, immediately available and complete. The user is responsible for ensuring that the products are suitable for the given application. It is FDT's right to change product specifications without notice. Property rights of third parties are to be considered. In addition, our particular sales and delivery terms are valid. The latest version of our product data sheet is obligatory, which can be requested directly through FDT. All information as well as all technical and drawing data comply with current technical standards and are based on our experience. National standards and regulations must be observed.

Technical changes reserved. As of 5th January 2026 | © 2026 FDT Flachdach Technologie GmbH, Mannheim, Germany