

# Technical Information Sheet



## Rhenofol CS

| Delivery form                                                                                         | Item Number |
|-------------------------------------------------------------------------------------------------------|-------------|
| 1 roll of Rhenofol CS 15.00 m x 1.03 m x 1.50 mm                                                      | 12 92 320   |
| <i>Note: For other colours and delivery options, please refer to the price list/product catalogue</i> |             |

### Description

Rhenofol CS is a homogeneous polymeric membrane consisting of PVC-P with an anti-slip embossing on the top.

### Application and processing

Rhenofol CS is used as a protective layer for maintenance and access routes on Rhenofol roofs. The construction of the roof in the area of the maintenance walkway must meet the technical requirements, particularly with regard to load-bearing capacity, deflection, thermal insulation and fixings, to ensure that no fixings can push through to the upper surface. The substrate must be solid, clean, and dry. The Rhenofol CS membrane is laid with the smooth side facing downwards. The water drainage on the roof should not be obstructed.

The seam sealing can be made with Rhenofol solvent welding agent (THF) or with a hot air welder. The Rhenofol CS must be welded tightly onto the Rhenofol roofing membrane all the way around.

### Properties

| Technical data       | Declared value         |
|----------------------|------------------------|
| Color                | anthracite             |
| Raw material basis:  | PVC-P                  |
| Nominal thickness:   | 1.5 mm                 |
| Membrane dimensions: | 15 m x 1.03 m x 1.5 mm |

- Anti-slip embossing
- Easy to install
- Not bitumen resistant
- U/V resistant

## Storage

Store material in the original packaging until installation. Carefully reseal any opened packaging units if they are to be stored outdoors. Store rolls in a horizontal position only. Protect rolls from direct sunlight, rain and snow.

## Shelf life

Unlimited, provided it is stored correctly.

## Packaging and disposal

Roll 15 m × 1.03 m, approx. 30 kg per roll  
Disposal codes/Waste code: 17 02 03 (plastics)

## Precautions and occupational safety

General safety regulations must be observed.

## Transport

General safety regulations must be observed.

*Please note: As our products are constantly evolving, please contact our technical department or visit [www.fdt.de](http://www.fdt.de) for the latest information on our products.*

### Legal Notice:

We refer emphatically to the fact, that all details mentioned, especially the application and utilization recommendation for the products and their system accessories, have been developed under normal conditions, and based on our knowledge and experience. Appropriate storage and usage of the products are assumed. A warranty or reliability of a finished project cannot be deduced because of varying materials, substrates and differing work conditions, neither by any indications nor from verbal statements, irrespective of any legal positions. For the possible accusation that FDT acted intentionally or grossly negligent, the user has to supply evidence that they provided FDT with all information and details necessary for an appropriate and correct evaluation through FDT in written form, immediately available and complete. The user is responsible for ensuring that the products are suitable for the given application. It is FDT's right to change product specifications without notice. Property rights of third parties are to be considered. In addition, our particular sales and delivery terms are valid. The latest version of our product data sheet is obligatory, which can be requested directly through FDT. All information as well as all technical and drawing data comply with current technical standards and are based on our experience. National standards and regulations must be observed.

Technical changes reserved. As of 5<sup>th</sup> January 2026 | © 2026 FDT Flachdach Technologie GmbH, Mannheim, Germany