

Technical Information Sheet



Rhenofol Paste

Delivery form	Item Number
2 kg container Rhenofol Paste light gray	12 81 060
2 kg container Rhenofol Paste anthracite	12 89 560

Description

Rhenofol paste is a liquid membrane based on soft PVC dissolved in a solvent, offering excellent UV and weather resistance.

Application and processing

Rhenofol paste is suitable for securing the edges of PVC-P roofing membranes and for fixing Rhenofol paving tiles and Rhenofol standing seam profiles to PVC-P roofing membranes.

The substrate must be dry and free of dust and grease. To apply the paste, it is best to transfer it into a polyethylene bottle (item no. 12 84 120) fitted with a nozzle.

Seam sealing: Apply a bead approximately 5 mm thick along the edges of the seam.

Standing seam profile: For Rhenofol standing seam profiles, apply a bead approximately 15 mm wide beneath the profile, insert the profile, and secure it using the pressure roller for standing seam profiles (item no. 12 88 980).

Paving tiles: For Rhenofol paving tiles, apply a strip of Rhenofol paste approximately 15 mm wide along the underside of the edges, lay the tiles in place, and then seal the edges of the tiles all the way round with Rhenofol paste.

The use of Rhenofol standing seam profiles and Rhenofol paving tiles is only recommended at temperatures above 20 °C, as otherwise they are too stiff, and the resulting stresses may lead to inadequate welds.

Consumption

Approx. 10 g/m for seam sealing, 30 g/m for standing seam profiles and 120 g/slab for paving tiles.

Resistance

Resistant to aging and light.

Properties

Technical data	Declared value
Color	gray, or see label for special colors
Consistence	pasty
Viscosity	approx. 360 mPas
Density	0.9369 g/cm ³
Thinner	Rhenofol solvent welding agent (THF)
At risk of frost	no

Storage

At + 15 °C to + 20 °C.

Shelf life

12 months at room temperature in the unopened original container.

Packaging and disposal

Tinplate container contents 2 kg.

Return empty containers to Interseroh (Recycling).

Waste code number unused product: 080409

Waste code number uncleaned packaging: 150110

Precautions and health and safety

See safety data sheet.

Transport

Information on transport labeling can be found in section 14 of the safety data sheet.

Please note: As our products are constantly evolving, please contact our technical department or visit www.fdt.de for the latest information on our products.

Legal Notice:

We refer emphatically to the fact, that all details mentioned, especially the application and utilization recommendation for the products and their system accessories, have been developed under normal conditions, and based on our knowledge and experience. Appropriate storage and usage of the products are assumed. A warranty or reliability of a finished project cannot be deduced because of varying materials, substrates and differing work conditions, neither by any indications nor from verbal statements, irrespective of any legal positions. For the possible accusation that FDT acted intentionally or grossly negligent, the user has to supply evidence that they provided FDT with all information and details necessary for an appropriate and correct evaluation through FDT in written form, immediately available and complete. The user is responsible for ensuring that the products are suitable for the given application. It is FDT's right to change product specifications without notice. Property rights of third parties are to be considered. In addition, our particular sales and delivery terms are valid. The latest version of our product data sheet is obligatory, which can be requested directly through FDT. All information as well as all technical and drawing data comply with current technical standards and are based on our experience. National standards and regulations must be observed.

Technical changes reserved. As of 5th January 2026 | © 2026 FDT Flachdach Technologie GmbH, Mannheim, Germany