

Technical Information Sheet



Rhenofol laminated metal sheet

Delivery form	Item Number
Stack of 10 sheets, 2.00 m x 1.00 m x 1.2 mm	12 61 510
Stack of 10 sheets, 3.00 m x 1.00 m x 1.2 mm	12 61 910
1 coil 30.00 m x 1.00 m x 1.2 mm	12 82 560
<i>Note: For other colours and delivery options, please refer to the price list/product catalogue</i>	

Description

Rhenofol laminated metal sheet is made of hot-dip galvanized sheet steel with a black protective coating on the back and Rhenofol C lamination on the top.

Application and processing

Rhenofol connecting sheet is used to manufacture profiles for extensions and end caps.

The Rhenofol laminated metal sheets can be cut and folded like normal steel sheets. The Rhenofol roofing membrane is welded onto the Rhenofol laminated metal sheets using hot-air or solvent welding. Eaves flashings made of Rhenofol laminated metal sheet metal must be fixed in a staggered pattern using suitable screws. For further information on installation, please refer to the Rhenofol application manual.

Properties

Technical data	Declared value
Thickness of steel sheet:	0.6 mm
Protective paint for the underside:	black
Thickness of Rhenofol C:	0.6 mm
Total thickness:	1.2 mm

Delivery form

stack of 5 sheets 2 × 1 m × 1.2 mm
 stack of 5 sheets 3 × 1 m × 1.2 mm
 stack of 10 sheets 2 × 1 m × 1.2 mm
 stack of 10 sheets 3 × 1 m × 1.2 mm
 stack of 30 sheets 2 × 1 m × 1.2 mm
 stack of 30 sheets 3 × 1 m × 1.2 mm
 30 × 1 m × 1.2 mm coil

Consumption

Consumption depends on the geometry of the areas of application. For further instructions, see the Rhenofol application manual.

Storage

Keep dry in its original packaging. The Rhenofol laminated metal sheets must be protected from moisture.

Shelf life

Unlimited, provided it is stored correctly.

Packaging and disposal

Disposal codes/Waste codes: 17 09 04 (mixed construction and demolition waste)

Precautions and occupational safety

General safety regulations must be observed.

Transport

General safety regulations must be observed.

Please note: As our products are constantly evolving, please contact our technical department or visit www.fdt.de for the latest information on our products.

Legal Notice:

We refer emphatically to the fact, that all details mentioned, especially the application and utilization recommendation for the products and their system accessories, have been developed under normal conditions, and based on our knowledge and experience. Appropriate storage and usage of the products are assumed. A warranty or reliability of a finished project cannot be deduced because of varying materials, substrates and differing work conditions, neither by any indications nor from verbal statements, irrespective of any legal positions. For the possible accusation that FDT acted intentionally or grossly negligent, the user has to supply evidence that they provided FDT with all information and details necessary for an appropriate and correct evaluation through FDT in written form, immediately available and complete. The user is responsible for ensuring that the products are suitable for the given application. It is FDT's right to change product specifications without notice. Property rights of third parties are to be considered. In addition, our particular sales and delivery terms are valid. The latest version of our product data sheet is obligatory, which can be requested directly through FDT. All information as well as all technical and drawing data comply with current technical standards and are based on our experience. National standards and regulations must be observed.

Technical changes reserved. As of 5th January 2026 | © 2026 FDT Flachdach Technologie GmbH, Mannheim, Germany