

Technical Information Sheet



Rhenofol thinner D

Delivery form	Item Number
5 kg container (approx. 5.7 l) Rhenofol thinner D	12 65 000

Description

Rhenofol Thinner D is a colourless solvent which is particularly suitable as a thinner and cleaning agent due to its special formulation.

Application and processing

Rhenofol contact adhesive 20 can be thinned with Rhenofol thinner D. The thinner is also suitable as a cleaning agent for application tools and Rhenofol roofing membranes (surface dirt).

Notes on processing

As a thinner:

The thinner is added in small quantities and stirred in well. Do not add more than 10 %.

As a cleaner:

The thinner is also suitable as a cleaning agent for application tools and Rhenofol roofing membranes. The Rhenofol swelling agent (THF) must be used for cleaning weathered Rhenofol roofing membranes.

Consumption

Do not add more than 10 %.

For cleaning approx. 15 g/m.

Properties

Technical data	Declared value
Color	colourless
Raw material basis	Ethyl acetate
Viscosity	0.50 mPas
Density	0.90 g/cm ³
Application temperature	optimal at +5 °C to +35 °C

Always observe the safety instructions on the container and in the safety data sheet.

Storage

Optimal at +5 °C to +20 °C; not sensitive to frost

Shelf life

Approx. 4 years at room temperature in the unopened original container.

Packaging and disposal

5 kg tinplate canister.

Waste code number uncleaned packaging: 150110

Precautions and health and safety

See safety data sheet.

Transport

Information on transport labeling can be found in section 14 of the safety data sheet.

Please note: As our products are constantly evolving, please contact our technical department or visit www.fdt.de for the latest information on our products.

Legal Notice:

We refer emphatically to the fact, that all details mentioned, especially the application and utilization recommendation for the products and their system accessories, have been developed under normal conditions, and based on our knowledge and experience. Appropriate storage and usage of the products are assumed. A warranty or reliability of a finished project cannot be deduced because of varying materials, substrates and differing work conditions, neither by any indications nor from verbal statements, irrespective of any legal positions. For the possible accusation that FDT acted intentionally or grossly negligent, the user has to supply evidence that they provided FDT with all information and details necessary for an appropriate and correct evaluation through FDT in written form, immediately available and complete. The user is responsible for ensuring that the products are suitable for the given application. It is FDT's right to change product specifications without notice. Property rights of third parties are to be considered. In addition, our particular sales and delivery terms are valid. The latest version of our product data sheet is obligatory, which can be requested directly through FDT. All information as well as all technical and drawing data comply with current technical standards and are based on our experience. National standards and regulations must be observed.

Technical changes reserved. As of 5th January 2026 | © 2026 FDT Flachdach Technologie GmbH, Mannheim, Germany