

Technical Information Sheet



Rhepanol h intensive cleaner

Delivery form	Item Number
2 kg container Rhepanol h intensive cleaner	17 30 210

Description

Rhepanol h intensive cleaner is a colorless solvent mixture for the pre-treatment of weathered PIB roofing membranes.

Application and processing

Rhepanol h intensive cleaner is designed for cleaning Rhepanol h roofing membranes that have been exposed to the weather for a long time and for diluting Rhepanol contact adhesive 50. The use of Rhepanol h intensive cleaner does not replace pre-treatment with Rhepanol h seam cleaner.

The surface to be treated must first be cleaned of coarse dirt, vegetation or other deposits.

The cleaner should preferably be applied to the weathered surface of Rhepanol h roofing membranes using protective gloves (item no. 17 50 040) and cleaning tissues (item no. 17 50 050), using light pressure, and then wiped off. Leave to dry thoroughly for about 1 hour. Pre-treat the seam area with Rhepanol h seam cleaner and then weld the seam using hot air.

Processing tools soiled with Rhepanol contact adhesive 50 can also be cleaned with Rhepanol h intensive cleaner.

If required, Rhepanol h intensive cleaner can also be used as a thinner for Rhepanol contact adhesive 50. However, add max. 5 % and stir in thoroughly (do not use electrical appliances).

Properties

Technical data	Declared value
Color	colorless
Consistence	thin
Density	0.875 g/cm ³

Consumption

Approx. 20 g/m (10 cm wide) are required for cleaning weathered Rhepanol surfaces. Consumption may vary depending on the weather and surface conditions.

Storage

at +5 °C to +20 °C, not susceptible to frost.

Shelf life

4 years in the unopened original container if stored properly.

Packaging and disposal

Tinplate container with press-fit bellows fitting contents 2 kg.

Waste code number unused product: 070104

Waste code number uncleaned packaging: 150110

Precautions and health and safety

Always observe the safety instructions on the container and in the safety data sheet.

Transport

Information on transport labeling can be found in section 14 of the safety data sheet.

Please note: As our products are constantly evolving, please contact our technical department or visit www.fdt.de for the latest information on our products.

Legal Notice:

We refer emphatically to the fact, that all details mentioned, especially the application and utilization recommendation for the products and their system accessories, have been developed under normal conditions, and based on our knowledge and experience. Appropriate storage and usage of the products are assumed. A warranty or reliability of a finished project cannot be deduced because of varying materials, substrates and differing work conditions, neither by any indications nor from verbal statements, irrespective of any legal positions. For the possible accusation that FDT acted intentionally or grossly negligent, the user has to supply evidence that they provided FDT with all information and details necessary for an appropriate and correct evaluation through FDT in written form, immediately available and complete. The user is responsible for ensuring that the products are suitable for the given application. It is FDT's right to change product specifications without notice. Property rights of third parties are to be considered. In addition, our particular sales and delivery terms are valid. The latest version of our product data sheet is obligatory, which can be requested directly through FDT. All information as well as all technical and drawing data comply with current technical standards and are based on our experience. National standards and regulations must be observed.

Technical changes reserved. As of 5th January 2026 | © 2026 FDT Flachdach Technologie GmbH, Mannheim, Germany