

Technical Information Sheet



Rhepanol h seam cleaner

Delivery form	Item Number
Rhepanol h seam cleaner	17 30 100

Description

Rhepanol h seam cleaner is a colorless solvent mixture.

Application and processing

Rhepanol h seam cleaner is used to clean or pre-treat the seams of Rhepanol hfk/hfk-bs/hg hot-air-weldable roofing membranes prior to hot-air welding.

Not suitable as a thinner for Rhepanol contact adhesive 50.

The seam cleaner is best used with protective gloves (item no. 17 50 040) and cleaning tissues (item no. 1750050) to clean the seams of Rhepanol h roofing membranes and prefabricated parts made from Rhepanol h. To do this, soak the cleaning tissues thoroughly so that both sides of the seam area can be cleaned in a single operation.

Properties

Technical data	Declared value
Color	colorless
Consistence	thin
Density	0.8569 g/cm ³

Consumption

A consumption of approx. 10 g/m can be assumed for cleaning the seam areas.

Storage

At temperatures between +5 °C and +20 °C; not susceptible to frost.

Shelf life

4 years in the unopened original container, provided it is stored correctly.

Packaging and disposal

Tinplate container with press-fit bellows fitting contents 5 kg.

Waste code number unused product: 070104

Waste code number uncleaned packaging: 150110

Precautions and health and safety

Always observe the safety instructions on the container and in the safety data sheet.

Transport

Information on transport labeling can be found in section 14 of the safety data sheet.

Please note: As our products are constantly evolving, please contact our technical department or visit www.fdt.de for the latest information on our products.

Legal Notice:

We refer emphatically to the fact, that all details mentioned, especially the application and utilization recommendation for the products and their system accessories, have been developed under normal conditions, and based on our knowledge and experience. Appropriate storage and usage of the products are assumed. A warranty or reliability of a finished project cannot be deduced because of varying materials, substrates and differing work conditions, neither by any indications nor from verbal statements, irrespective of any legal positions. For the possible accusation that FDT acted intentionally or grossly negligent, the user has to supply evidence that they provided FDT with all information and details necessary for an appropriate and correct evaluation through FDT in written form, immediately available and complete. The user is responsible for ensuring that the products are suitable for the given application. It is FDT's right to change product specifications without notice. Property rights of third parties are to be considered. In addition, our particular sales and delivery terms are valid. The latest version of our product data sheet is obligatory, which can be requested directly through FDT. All information as well as all technical and drawing data comply with current technical standards and are based on our experience. National standards and regulations must be observed.

Technical changes reserved. As of 5th January 2026 | © 2026 FDT Flachdach Technologie GmbH, Mannheim, Germany