

Technical Information Sheet



Rhepanol h

Delivery form	Item Number
1 roll of Rhepanol h 20.00 m x 0.50 m x 1.80 mm	17 08 900

Description

Homogeneous strips made of PIB for detailing, suitable for the Rhepanol hfk/hg roofing membrane system. The strips are supplied in rolls (20.00 m x 0.50 m). The material thickness is 1.80 mm. The top side of the waterproofing membrane is gray, the bottom side is black.

Application and processing

The material is used to form connections, such as round pipe penetrations, where the material has to be heated and stretched. Membranes with interlinings, reinforcements or fleece backing cannot usually be used for such applications. However, special applications are also possible, such as pipe cladding, window flashings, etc.

After being cleaned with Rhepanol h seam cleaner, the Rhepanol h material is homogeneously welded together using hot air.

Properties

Technical data	Test standard	results
Reaction to fire	EN ISO 11925-2	Class E
	EN 13501-1	
Color of top layer		gray
Color of bottom layer		black
Total thickness		1.8 mm

Consumption

Consumption depends on the size and number of details.

Storage

Store material in the original packaging until installation. Carefully reseal any opened packaging units if they are to be stored outdoors. Store rolls in a horizontal position only. Protect rolls from direct sunlight, rain and snow.

Shelf life

Unlimited, provided it is stored correctly.

Packaging and disposal

Disposal codes/Waste code: 17 02 03 (plastics)

Precautions and occupational safety

General safety regulations must be observed.

Transport

General safety regulations must be observed.

Please note: As our products are constantly evolving, please contact our technical department or visit www.fdt.de for the latest information on our products.

Legal Notice:

We refer emphatically to the fact, that all details mentioned, especially the application and utilization recommendation for the products and their system accessories, have been developed under normal conditions, and based on our knowledge and experience. Appropriate storage and usage of the products are assumed. A warranty or reliability of a finished project cannot be deduced because of varying materials, substrates and differing work conditions, neither by any indications nor from verbal statements, irrespective of any legal positions. For the possible accusation that FDT acted intentionally or grossly negligent, the user has to supply evidence that they provided FDT with all information and details necessary for an appropriate and correct evaluation through FDT in written form, immediately available and complete. The user is responsible for ensuring that the products are suitable for the given application. It is FDT's right to change product specifications without notice. Property rights of third parties are to be considered. In addition, our particular sales and delivery terms are valid. The latest version of our product data sheet is obligatory, which can be requested directly through FDT. All information as well as all technical and drawing data comply with current technical standards and are based on our experience. National standards and regulations must be observed.

Technical changes reserved. As of 5th January 2026 | © 2026 FDT Flachdach Technologie GmbH, Mannheim, Germany