

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### Dichtungsmasse S

Revision: 09.04.2025

Product code: FDT-034

Page 1 of 12

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1. Product identifier

Dichtungsmasse S

UFI: MMYH-6N4M-200K-1FP6

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

#### Use of the substance/mixture

joint sealant

#### Uses advised against

Only use for the intended purpose.

The product is intended for professional use.

### 1.3. Details of the supplier of the safety data sheet

Company name:	FDT Flachdach Technologie GmbH	
Street:	Eisenbahnstraße 6-8	
Place:	D-68199 Mannheim	
Telephone:	+49 (621) 8504100	Telefax: +49 (621) 8504200
E-mail:	kundenservice@fdt.de	
Contact person:	Fachkraft für Arbeitssicherheit	Telephone: +49 (621) 8504303
E-mail:	gefahrstoffe@fdt.de	
Internet:	http://www.fdt.de	
Responsible Department:	Arbeitssicherheit und Umweltschutz	

### 1.4. Emergency telephone number:

Emergency Action: In the event of a medical enquiry involving this product, please contact your doctor or local hospital accident and emergency department or the NHS enquiry service. This safety data sheet is an English translation of the EU safety data sheet and is not suitable for the distribution in a specific country.

## SECTION 2: Hazards identification

### 2.1. Classification of the substance or mixture

#### Regulation (EC) No 1272/2008

Flam. Liq. 3; H226

STOT SE 3; H336

Full text of hazard statements: see SECTION 16.

### 2.2. Label elements

#### Regulation (EC) No 1272/2008

#### Hazard components for labelling

n-butyl acetate

Signal word: Warning

#### Pictograms:



#### Hazard statements

H226

Flammable liquid and vapour.

H336

May cause drowsiness or dizziness.

#### Precautionary statements

P210

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

# Safety Data Sheet

according to Regulation (EC) No 1907/2006

## Dichtungsmasse S

Revision: 09.04.2025

Product code: FDT-034

Page 2 of 12

P233	smoking.
P261	Keep container tightly closed.
P280	Avoid breathing dust/fume/gas/mist/vapours/spray.
P303+P361+P353	Wear protective gloves and eye protection/face protection.
P304+P340	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.
P305+P351+P338	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P501	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
	Dispose of contents/container to an appropriate recycling or disposal facility.

### Special labelling of certain mixtures

EUH066	Repeated exposure may cause skin dryness or cracking.
--------	---

### 2.3. Other hazards

In use, may form flammable/explosive vapour-air mixture.

The product does not meet the PBT or vPvB criteria in Annex XIII of the REACH Regulation.

This product does not contain a substance that has endocrine disrupting properties with respect to humans as no components meets the criteria.

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

## SECTION 3: Composition/information on ingredients

### 3.2. Mixtures

#### Relevant ingredients

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification (Regulation (EC) No 1272/2008)			
64742-54-7	Baseoil - unspecified, Distillates (petroleum), hydrotreated heavy paraffinic			35 - < 40 %
	265-157-1	649-467-00-8	01-2119484627-25	
	Asp. Tox. 1; H304			
123-86-4	n-butyl acetate			25 - < 30 %
	204-658-1	607-025-00-1	01-2119485493-29	
	Flam. Liq. 3, STOT SE 3; H226 H336 EUH066			
52829-07-9	bis(2,2,6,6-tetramethyl-4-piperidyl) sebacate			0.2 - < 0.3 %
	258-207-9		01-2119537297-32	
	Eye Dam. 1, Aquatic Acute 1, Aquatic Chronic 2; H318 H400 H411			

Full text of H and EUH statements: see section 16.

#### Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
		Specific Conc. Limits, M-factors and ATE	
123-86-4	204-658-1	n-butyl acetate	25 - < 30 %
		inhalation: LC50 = >21 mg/l (vapours); dermal: LD50 = >17600 mg/kg; oral: LD50 = 13100 mg/kg	

#### Further Information

Note (CAS 64742-54-7): The classification as a carcinogen need not apply if it can be shown that the substance contains less than 3 % DMSO extract as measured by IP 346 "Determination of polycyclic aromatics in unused lubricating base oils and asphaltene free petroleum fractions — Dimethyl sulphoxide extraction refractive index method", Institute of Petroleum, London. This note applies only to certain complex oil-derived substances in Part 3.

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

**Dichtungsmasse S**

Revision: 09.04.2025

Product code: FDT-034

Page 3 of 12

**SECTION 4: First aid measures****4.1. Description of first aid measures****General information**

In case of troubles or persistent symptoms, consult an doctor/physician.

Remove persons from danger area and lie them down. Never orally infuse something to an unconscious person. No special first aid measures necessary. A vomiting, supine person must be brought into recovery position.

**After inhalation**

Provide fresh air. In case of respiratory tract irritation, consult a physician.

In case of irregular breathing or respiratory arrest, perform artificial respiration.

**After contact with skin**

After contact with skin, wash immediately with plenty of water and soap. Change contaminated clothing. In case of skin irritation, consult a physician.

**After contact with eyes**

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

**After ingestion**

Rinse mouth, spit liquid again. Do NOT induce vomiting. Let water be drunken in little sips (dilution effect). Call a physician immediately. Do NOT induce vomiting. Aspiration hazard.

**4.2. Most important symptoms and effects, both acute and delayed**

May cause drowsiness or dizziness. Repeated exposure may cause skin dryness or cracking.

**4.3. Indication of any immediate medical attention and special treatment needed**

Treat symptomatically.

**SECTION 5: Firefighting measures****5.1. Extinguishing media****Suitable extinguishing media**

Carbon dioxide (CO<sub>2</sub>). Extinguishing powder. Water spray. Fight larger fires with water spray jet or alcohol-resistant foam.

**Unsuitable extinguishing media**

High power water jet.

**5.2. Special hazards arising from the substance or mixture**

Vapours may form explosive mixtures with air. Vapours are heavier than air and will spread at floor level.

Thermal decomposition can lead to harmful gases and vapours.

**5.3. Advice for firefighters**

Co-ordinate fire-fighting measures to the fire surroundings. Wear a self-contained breathing apparatus and chemical protective clothing.

**Additional information**

Do not allow to enter into surface water or drains.

**SECTION 6: Accidental release measures****6.1. Personal precautions, protective equipment and emergency procedures****General advice**

Provide adequate ventilation. Keep away from sources of ignition - No smoking.

Avoid contact with skin, eyes and clothes. Wear personal protection equipment.

**6.2. Environmental precautions**

Do not allow to enter into surface water or drains.

In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### Dichtungsmasse S

Revision: 09.04.2025

Product code: FDT-034

Page 4 of 12

#### 6.3. Methods and material for containment and cleaning up

##### For containment

Take up mechanically. Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).

##### For cleaning up

Clean contaminated articles and floor according to the environmental legislation.

#### 6.4. Reference to other sections

Safe handling: see section 7

Personal precautions: refer to section 8

Disposal: see section 13

### SECTION 7: Handling and storage

#### 7.1. Precautions for safe handling

##### Advice on safe handling

Provide adequate ventilation as well as local exhaust at critical locations. Handle and open container with care.

Avoid the formation of aerosol.

##### Advice on protection against fire and explosion

Keep away from sources of ignition - No smoking. Take precautionary measures against static discharges.

##### Advice on general occupational hygiene

Change contaminated clothing. Wash hands before breaks and after work. When using do not eat or drink.

Avoid contact with skin, eyes and clothes. After contact with skin, wash immediately with plenty of water and soap or a suitable cleaning agent.

#### 7.2. Conditions for safe storage, including any incompatibilities

##### Requirements for storage rooms and vessels

Store only in original container. Keep container tightly closed in a cool, well-ventilated place.

#### 7.3. Specific end use(s)

joint sealant

### SECTION 8: Exposure controls/personal protection

#### 8.1. Control parameters

##### Occupational exposure limits

CAS No	Substance	ppm	mg/m <sup>3</sup>	fib/cm <sup>3</sup>	Category	Origin
123-86-4	n-Butyl acetate	50	241		TWA (8 h)	
		150	723		STEL (15 min)	

##### DNEL/DMEL values

CAS No	Substance	Exposure route	Effect	Value
123-86-4	n-butyl acetate			
Consumer DNEL, acute		inhalation		859,7 mg/m <sup>3</sup>
Consumer DNEL, long-term		inhalation		102,34 mg/m <sup>3</sup>
Worker DNEL, acute		inhalation		960 mg/m <sup>3</sup>
Worker DNEL, long-term		inhalation		480 mg/m <sup>3</sup>

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### Dichtungsmasse S

Revision: 09.04.2025

Product code: FDT-034

Page 5 of 12

#### PNEC values

CAS No	Substance	
Environmental compartment		Value
123-86-4	n-butyl acetate	
Freshwater		0,18 mg/l
Marine water		0,018 mg/l
Freshwater sediment		0,981 mg/kg
Marine sediment		0,0981 mg/kg
Micro-organisms in sewage treatment plants (STP)		35,6 mg/l
Soil		0,0903 mg/kg

#### 8.2. Exposure controls

##### Appropriate engineering controls

Ensure adequate ventilation.

##### Individual protection measures, such as personal protective equipment

##### Eye/face protection

Tightly fitting safety glasses with side shields.

##### Hand protection

Protect skin by using skin protective cream. Wear suitable gloves.

When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits.

The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances.

Suitable material: NBR (Nitrile rubber). PVC (Polyvinyl chloride).

Thickness of glove material: 0,9 mm

penetration time (maximum wearing period): 30min

##### Skin protection

Full cover clothing covering arms and legs.

##### Respiratory protection

Use protective filter mask in case of short-term and low exposure; in case of intense or longer exposure, use respiratory protection device operating independently from circulating air.

### SECTION 9: Physical and chemical properties

#### 9.1. Information on basic physical and chemical properties

Physical state:	viscous	
Colour:	according to product description	
Odour:	like gasoline	
Melting point/freezing point:		not determined
Boiling point or initial boiling point and boiling range:		126 °C
Flammability:		not determined
Lower explosion limits:		1,2 vol. %
Upper explosion limits:		7,5 vol. %
Flash point:		27 °C
Auto-ignition temperature:		not determined
Decomposition temperature:		not determined
pH-Value:		6,2
Viscosity / kinematic:		not determined
Water solubility:		insoluble

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

**Dichtungsmasse S**

Revision: 09.04.2025

Product code: FDT-034

Page 6 of 12

Partition coefficient n-octanol/water:	not determined
Vapour pressure: (at 20 °C)	15 hPa
Density (at 20 °C):	0,93 g/cm <sup>3</sup>
Relative vapour density:	not determined

**9.2. Other information****Information with regard to physical hazard classes****Explosive properties**

The product is not explosive, however, formation of explosive mixtures are possible.

**Self-ignition temperature****Gas:**

not determined

**Oxidizing properties**

not determined

**Other safety characteristics****Solvent content:**

~24 %

**Viscosity / dynamic:**

15000 mPa·s

(at 20 °C)

**Further Information**

No further data available.

**SECTION 10: Stability and reactivity****10.1. Reactivity**

No dangerous reactivity under regular conditions.

**10.2. Chemical stability**

The product is stable under regular conditions.

**10.3. Possibility of hazardous reactions**

No known hazardous reactions.

**10.4. Conditions to avoid**

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

**10.5. Incompatible materials**

Keep away from strong acids, strong bases and strong oxidisers to avoid exothermic reactions.

**10.6. Hazardous decomposition products**

Thermal decomposition can lead to harmful gases and vapours.

**SECTION 11: Toxicological information****11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008****Acute toxicity**

Based on available data, the classification criteria are not met.

**ATEmix calculated**

ATE (oral) > 2000 mg/kg; ATE (dermal) > 2000 mg/kg; ATE (inhalation vapour) > 20 mg/l; ATE (inhalation dust/mist) > 5 mg/l

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### Dichtungsmasse S

Revision: 09.04.2025

Product code: FDT-034

Page 7 of 12

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
123-86-4	n-butyl acetate				
	oral	LD50 mg/kg	13100	Rat	
	dermal	LD50 mg/kg	>17600	Rabbit	
	inhalation (4 h) vapour	LC50	>21 mg/l	Rat	

#### Irritation and corrosivity

Skin corrosion/irritation: Based on available data, the classification criteria are not met.

Serious eye damage/eye irritation: Based on available data, the classification criteria are not met.

Repeated exposure may cause skin dryness or cracking.

#### Sensitising effects

Based on available data, the classification criteria are not met.

#### Carcinogenic/mutagenic/toxic effects for reproduction

Germ cell mutagenicity: Based on available data, the classification criteria are not met.

Carcinogenicity: Based on available data, the classification criteria are not met.

Reproductive toxicity: Based on available data, the classification criteria are not met.

#### STOT-single exposure

May cause drowsiness or dizziness. (n-butyl acetate)

#### STOT-repeated exposure

Based on available data, the classification criteria are not met.

#### Aspiration hazard

Based on available data, the classification criteria are not met.

### 11.2. Information on other hazards

#### Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to humans as no components meets the criteria.

## SECTION 12: Ecological information

### 12.1. Toxicity

Toxic to aquatic life with long lasting effects.

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h]   [d]	Species	Source	Method
123-86-4	n-butyl acetate					
	Acute fish toxicity	LC50	62 mg/l	96 h	Leuciscus idus (golden orfe)	
	Acute algae toxicity	ErC50	674 mg/l	72 h	Scenedesmus subspicatus	

### 12.2. Persistence and degradability

No data available.

### 12.3. Bioaccumulative potential

No data available.

### 12.4. Mobility in soil

No data available.

### 12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### Dichtungsmasse S

Revision: 09.04.2025

Product code: FDT-034

Page 8 of 12

#### 12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

#### 12.7. Other adverse effects

No data available.

### SECTION 13: Disposal considerations

#### 13.1. Waste treatment methods

##### Disposal recommendations

Disposal according to official regulations.

Consult the local waste disposal expert about waste disposal. According to EAKV, allocation of waste identity numbers/waste descriptions must be carried out in a specific way for every industry and process.

##### List of Wastes Code - residues/unused products

080111 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU and removal of paint and varnish; waste paint and varnish containing organic solvents or other hazardous substances; hazardous waste

##### List of Wastes Code - used product

080111 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU and removal of paint and varnish; waste paint and varnish containing organic solvents or other hazardous substances; hazardous waste

##### List of Wastes Code - contaminated packaging

150110 WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED; packaging (including separately collected municipal packaging waste); packaging containing residues of or contaminated by hazardous substances; hazardous waste

##### Contaminated packaging

Non-contaminated packages may be recycled. Handle contaminated packages in the same way as the substance itself.

### SECTION 14: Transport information

#### Land transport (ADR/RID)

**14.1. UN number or ID number:** UN 1263

**14.2. UN proper shipping name:** Paint

**14.3. Transport hazard class(es):** 3

**14.4. Packing group:** II

Hazard label: 3



Classification code: F1

Special Provisions: 163 367 640D 650

Limited quantity: 5 L

Excepted quantity: E2

Transport category: 2

Hazard No: 33

Tunnel restriction code: D/E

#### Inland waterways transport (ADN)

**14.1. UN number or ID number:** UN 1263



## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### Dichtungsmasse S

Revision: 09.04.2025

Product code: FDT-034

Page 9 of 12

**14.2. UN proper shipping name:**

Paint

**14.3. Transport hazard class(es):**

3

**14.4. Packing group:**

II

Hazard label:

3



Classification code:

F1

Special Provisions:

163 367 640D 650

Limited quantity:

5 L

Excepted quantity:

E2

**Marine transport (IMDG)**

**14.1. UN number or ID number:**

UN 1263

**14.2. UN proper shipping name:**

Paint

**14.3. Transport hazard class(es):**

3

**14.4. Packing group:**

II

Hazard label:

3



Marine pollutant:

Ja

Special Provisions:

163, 367

Limited quantity:

5 L

Excepted quantity:

E2

EmS:

F-E, S-E

**Air transport (ICAO-TI/IATA-DGR)**

**14.1. UN number or ID number:**

UN 1263

**14.2. UN proper shipping name:**

Paint

**14.3. Transport hazard class(es):**

3

**14.4. Packing group:**

II

Hazard label:

3



Special Provisions:

A3 A72 A192

Limited quantity Passenger:

1 L

Passenger LQ:

Y341

Excepted quantity:

E2

IATA-packing instructions - Passenger:

353

IATA-max. quantity - Passenger:

5 L

IATA-packing instructions - Cargo:

364

IATA-max. quantity - Cargo:

60 L

**14.5. Environmental hazards**

ENVIRONMENTALLY HAZARDOUS:

No

**14.6. Special precautions for user**

No special precautions known.

**14.7. Maritime transport in bulk according to IMO instruments**

not applicable

## SECTION 15: Regulatory information

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

**Dichtungsmasse S**

Revision: 09.04.2025

Product code: FDT-034

Page 10 of 12

**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture****EU regulatory information**

Restrictions on use (REACH, annex XVII):

Entry 40, Entry 75

Directive 2004/42/EC on VOC in  
paints and varnishes: 24 %**Additional information**

Regulation (EC) No. 1005/2009 on substances that lead to the depletion of the ozone layer: not applicable

Regulation (EC) No. 648/2004 [Detergents regulation]: not applicable

Regulation (EC) No 2019/1021 on persistent organic pollutants: not applicable

Regulation (EC) No 649/2012 of the European Parliament and of the Council concerning the export and import of dangerous chemicals: This mix contains no chemicals that are subject to the export notification procedures (annex 1).

This mixture contains the following substances of very high concern (SVHC) which are included in the

Candidate List according to Article 59 of REACH: none

This mixture contains the following substances of very high concern (SVHC) which are subject to authorisation according to Annex XIV of REACH: none

**National regulatory information**

Employment restrictions:

Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC). Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.

Water hazard class (D):

1 - slightly hazardous to water

**Additional information**

Observe in addition any national regulations!

**15.2. Chemical safety assessment**

For the following substances of this mixture a chemical safety assessment has been carried out:

Baseoil - unspecified, Distillates (petroleum), hydrotreated heavy paraffinic

n-butyl acetate

**SECTION 16: Other information****Changes**

This data sheet contains changes from the previous version in section(s): 2,3,4,6,7,8,9,11,12,13,14,15,16.

Version 1,00 - Creation - 25.01.2013

Version 1,01 - Classification/Labeling according Regulation No.1272/2008 (GHS/CLP) and general revision - 27.07.2015

Version 1,02 - changes in section 2 and 3 - 31.08.2018

Version 1,03 - Change and revision of the SDS because of new information / recipe. Replaces SDS with identifier RCSO-FDT-027 - 26.10.2018

Version 1,04 - General update - 21.01.2021

Version 1,05 - General update - 09.04.2025

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### Dichtungsmasse S

Revision: 09.04.2025

Product code: FDT-034

Page 11 of 12

#### Abbreviations and acronyms

Flam. Liq. 3: Flammable liquids, hazard category 3  
 Asp. Tox. 1: Aspiration hazard, hazard category 1  
 Eye Dam. 1: Serious eye damage, hazard category 1  
 STOT SE 3: Specific target organ toxicity - single exposure, hazard category 3  
 Aquatic Acute 1: Hazardous to the aquatic environment, hazard category: Acute 1  
 Aquatic Chronic 2: Hazardous to the aquatic environment, long-term hazard category: Chronic 2  
 ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)  
 BImSchV (Fed.Imm.Prot.Act): Directive on the Implementation of the Federal Immission Protection Act  
 CAS: Chemical Abstracts Service  
 DIN: Norm of the Deutsche Institut für Normung (German Institute for Standardization)  
 EC: Effective Concentration  
 EG: European Community (Europäische Gemeinschaft)  
 EN: European Norm  
 IATA: International Air Transport Association  
 IBC Code: International Code for the Construction and Equipment of ships carrying Dangerous Chemicals in Bulk  
 ICAO: International Civil Aviation Organization  
 IMDG: International Maritime Code for Dangerous Goods  
 ISO: Norm of the International Standards Organization  
 CLP: Classification, Labeling, Packaging  
 IUCLID: International Uniform Chemical Information Database  
 LC: Lethal concentration  
 LD: Lethal dose  
 log Kow: Octanol/water partition coefficient  
 MARPOL: Maritime Pollution Convention = Convention for the Prevention of Maritime Pollution from Ships  
 OECD: Organisation for Economic Co-operation and Development  
 PBT: Persistent, bio-cumulative, toxic  
 RID: Regulation Concerning the International Transport of Dangerous Goods by Rail  
 TRGS: Technische Regeln für Gefahrstoffe  
 UN: United Nations  
 VOC: Volatile Organic Compounds  
 vPvB: very persistent and very bio-cumulative  
 WGK: German Water Hazard Class  
 GHS: Globally Harmonized System of Classification and Labelling of Chemicals  
 EINECS: European Inventory of Existing Commercial Chemical Substances  
 ELINCS: European List of Notified Chemical Substances  
 DNEL: Derived No Effect Level  
 PNEC: Predicted No Effect Concentration  
 TLV: Threshold Limiting Value  
 STOT: Specific Target Organ Toxicity  
 AwSV: Ordinance on Installations for Handling Substances Hazardous to Water

#### Classification for mixtures and used evaluation method according to Regulation (EC) No 1272/2008 [CLP]

Classification	Classification procedure
Flam. Liq. 3; H226	On basis of test data
STOT SE 3; H336	Calculation method

#### Relevant H and EUH statements (number and full text)

H226 Flammable liquid and vapour.  
 H304 May be fatal if swallowed and enters airways.  
 H318 Causes serious eye damage.  
 H336 May cause drowsiness or dizziness.  
 H400 Very toxic to aquatic life.  
 H411 Toxic to aquatic life with long lasting effects.

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### Dichtungsmasse S

Revision: 09.04.2025

Product code: FDT-034

Page 12 of 12

EUH066 Repeated exposure may cause skin dryness or cracking.

#### Further Information

The information given in this safety data sheet is to describe the product's safety regulations. It is not for guaranteeing certain characteristics and is based on today's knowledge. The safety data sheet was generated upon information of pre-suppliers by:

asseso AG, Ottostraße 1, 63741, Aschaffenburg, Germany

Phone: +49 (0)6021 - 1 50 86-0, Fax: +49 (0)6021 - 1 50 86-77, E-Mail: eu-sds@asseso.eu, www.asseso.eu

---

*(The data for the relevant ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)*