

Safety Data Sheet

according to Regulation (EC) No 1907/2006

FDT Dachbahnenkleber

Revision: 09.04.2025

Product code: FDT-001

Page 1 of 13

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

FDT Dachbahnenkleber

UFI: M4PE-JPDC-X00E-W7XC

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

adhesives

Uses advised against

Only use for the intended purpose.

The product is intended for professional use.

1.3. Details of the supplier of the safety data sheet

Company name:	FDT Flachdach Technologie GmbH	
Street:	Eisenbahnstraße 6-8	
Place:	D-68199 Mannheim	
Telephone:	+49 (621) 8504100	Telefax: +49 (621) 8504200
E-mail:	kundenservice@fdt.de	
Contact person:	Fachkraft für Arbeitssicherheit	Telephone: +49 (621) 8504303
E-mail:	gefahrstoffe@fdt.de	
Internet:	http://www.fdt.de	
Responsible Department:	Arbeitssicherheit und Umweltschutz	

1.4. Emergency telephone number:

Emergency Action: In the event of a medical enquiry involving this product, please contact your doctor or local hospital accident and emergency department or the NHS enquiry service. This safety data sheet is an English translation of the EU safety data sheet and is not suitable for the distribution in a specific country.

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No 1272/2008

Flam. Liq. 2; H225
Carc. 2; H351
Skin Irrit. 2; H315
Eye Irrit. 2; H319
Resp. Sens. 1; H334
Skin Sens. 1; H317
STOT SE 3; H336
STOT RE 2; H373

Full text of hazard statements: see SECTION 16.

2.2. Label elements

Regulation (EC) No 1272/2008

Hazard components for labelling

Diphenylmethanediisocyanate - Isomers & Homologues

Signal word: Danger

Pictograms:



Safety Data Sheet

according to Regulation (EC) No 1907/2006

FDT Dachbahnenkleber

Revision: 09.04.2025

Product code: FDT-001

Page 2 of 13

Hazard statements

H225	Highly flammable liquid and vapour.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H336	May cause drowsiness or dizziness.
H351	Suspected of causing cancer.
H373	May cause damage to organs through prolonged or repeated exposure.

Precautionary statements

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P243	Take action to prevent static discharges.
P260	Do not breathe dust/fume/gas/mist/vapours/spray.
P262	Do not get in eyes, on skin, or on clothing.
P280	Wear protective gloves and eye protection/face protection.
P301+P310	IF SWALLOWED: Immediately call a POISON CENTER/doctor.
P331	Do NOT induce vomiting.
P303+P361+P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water.
P304+P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P501	Dispose of contents/container to an appropriate recycling or disposal facility.

Special labelling of certain mixtures

EUH204	Contains isocyanates. May produce an allergic reaction.
--------	---

2.3. Other hazards

The product does not meet the PBT or vPvB criteria in Annex XIII of the REACH Regulation.

This product does not contain a substance that has endocrine disrupting properties with respect to humans as no components meets the criteria.

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

SECTION 3: Composition/information on ingredients**3.2. Mixtures**

Safety Data Sheet

according to Regulation (EC) No 1907/2006

FDT Dachbahnenkleber

Revision: 09.04.2025

Product code: FDT-001

Page 3 of 13

Relevant ingredients

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification (Regulation (EC) No 1272/2008)			
9016-87-9	Diphenylmethanediisocyanate - Isomers & Homologues			5-10 %
	Carc. 2, Acute Tox. 4, Skin Irrit. 2, Eye Irrit. 2, Resp. Sens. 1, Skin Sens. 1, STOT SE 3, STOT RE 2; H351 H332 H315 H319 H334 H317 H335 H373			
79-20-9	methyl acetate			5-10 %
	201-185-2	607-021-00-X	01-2119459211-47	
	Flam. Liq. 2, Eye Irrit. 2, STOT SE 3; H225 H319 H336 EUH066			
141-78-6	ethyl acetate			2,5-5 %
	205-500-4	607-022-00-5	01-2119475103-46	
	Flam. Liq. 2, Eye Irrit. 2, STOT SE 3; H225 H319 H336 EUH066			
	Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane			<2,5 %
	921-024-6		01-2119475514-35	
	Flam. Liq. 2, Skin Irrit. 2, STOT SE 3, Asp. Tox. 1, Aquatic Chronic 2; H225 H315 H336 H304 H411			

Full text of H and EUH statements: see section 16.

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
	Specific Conc. Limits, M-factors and ATE		
9016-87-9		Diphenylmethanediisocyanate - Isomers & Homologues	5-10 %
	inhalation: ATE = 11 mg/l (vapours); inhalation: ATE = 1,5 mg/l (dusts or mists)		
141-78-6	205-500-4	ethyl acetate	2,5-5 %
	dermal: LD50 = >20000 mg/kg; oral: LD50 = 4100 mg/kg		

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

In case of troubles or persistent symptoms, consult an doctor/physician.

Remove persons from danger area and lie them down. Never orally infuse something to an unconscious person. No special first aid measures necessary. A vomiting, supine person must be brought into recovery position.

After inhalation

Provide fresh air. In case of respiratory tract irritation, consult a physician.

In case of irregular breathing or respiratory arrest, perform artificial respiration.

After contact with skin

After contact with skin, wash immediately with plenty of water and soap. Change contaminated clothing. In case of skin irritation, consult a physician.

After contact with eyes

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

After ingestion

Rinse mouth, spit liquid again. Do NOT induce vomiting. Let water be drunken in little sips (dilution effect). Call a physician immediately. Do NOT induce vomiting. Aspiration hazard.

4.2. Most important symptoms and effects, both acute and delayed

Causes skin irritation.

May cause an allergic skin reaction.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

FDT Dachbahnenkleber

Revision: 09.04.2025

Product code: FDT-001

Page 4 of 13

Causes serious eye irritation.
May cause allergy or asthma symptoms or breathing difficulties if inhaled.
May cause damage to organs through prolonged or repeated exposure.
Suspected of causing cancer.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Extinguishing powder.

Unsuitable extinguishing media

Water.

High power water jet.

5.2. Special hazards arising from the substance or mixture

Thermal decomposition can lead to harmful gases and vapours.

5.3. Advice for firefighters

Co-ordinate fire-fighting measures to the fire surroundings. Wear a self-contained breathing apparatus and chemical protective clothing.

Additional information

Do not allow to enter into surface water or drains.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General advice

Provide adequate ventilation. Avoid contact with skin, eyes and clothes. Wear personal protection equipment.

6.2. Environmental precautions

Do not allow to enter into surface water or drains.

In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

6.3. Methods and material for containment and cleaning up

For containment

Take up mechanically. Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).

For cleaning up

Clean contaminated articles and floor according to the environmental legislation.

6.4. Reference to other sections

Safe handling: see section 7

Personal precautions: refer to section 8

Disposal: see section 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Provide adequate ventilation as well as local exhaust at critical locations. Handle and open container with care.

Avoid the formation of aerosol.

Advice on protection against fire and explosion

Keep away from sources of ignition - No smoking.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

FDT Dachbahnenkleber

Revision: 09.04.2025

Product code: FDT-001

Page 5 of 13

Advice on general occupational hygiene

Wear personal protection equipment.

Change contaminated clothing. Wash hands before breaks and after work. When using do not eat or drink.

Avoid contact with skin, eyes and clothes. After contact with skin, wash immediately with plenty of water and soap or a suitable cleaning agent.

Do not put any product-impregnated cleaning rags into your trouser pockets.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Store only in original container. Keep container tightly closed in a cool, well-ventilated place.

7.3. Specific end use(s)

adhesives

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits

CAS No	Substance	ppm	mg/m ³	fib/cm ³	Category	Origin
141-78-6	Ethyl acetate	200	734		TWA (8 h)	
		400	1468		STEL (15 min)	
79-20-9	Methyl acetate	200	610		TWA (8 h)	
		250	760		STEL (15 min)	

DNEL/DMEL values

CAS No	Substance			
DNEL type		Exposure route	Effect	Value
79-20-9	methyl acetate			
Worker DNEL, long-term		inhalation	systemic	300 mg/m³
Worker DNEL, acute		inhalation	systemic	3777 mg/m³
Worker DNEL, long-term		inhalation	local	620 mg/m³
Worker DNEL, long-term		dermal	systemic	43 mg/kg bw/day
141-78-6	ethyl acetate			
Worker DNEL, acute		inhalation	systemic	1468 mg/m³
Worker DNEL, long-term		dermal	systemic	63 mg/kg bw/day
Consumer DNEL, long-term		dermal	systemic	37 mg/kg bw/day
Worker DNEL, long-term		inhalation	systemic	734 mg/m³
Consumer DNEL, long-term		oral	systemic	4,5 mg/kg bw/day
Consumer DNEL, acute		inhalation	systemic	734 mg/m³
Consumer DNEL, long-term		inhalation	systemic	367 mg/m³
	Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane			
Worker DNEL, long-term		dermal		300 mg/kg bw/day
Worker DNEL, long-term		inhalation		2085 mg/m³
Consumer DNEL, long-term		oral		149 mg/kg bw/day
Consumer DNEL, long-term		dermal		149 mg/kg bw/day
Consumer DNEL, long-term		inhalation		447 mg/m³

Safety Data Sheet

according to Regulation (EC) No 1907/2006

FDT Dachbahnenkleber

Revision: 09.04.2025

Product code: FDT-001

Page 6 of 13

PNEC values

CAS No	Substance	
Environmental compartment		Value
141-78-6	ethyl acetate	
Freshwater		0,26 mg/l
Marine water		0,026 mg/l
Freshwater sediment		1,25 mg/kg
Marine sediment		0,125 mg/kg
Secondary poisoning		200 mg/kg
Micro-organisms in sewage treatment plants (STP)		650 mg/l
Soil		0,24 mg/kg

8.2. Exposure controls

Appropriate engineering controls

Ensure adequate ventilation.

Individual protection measures, such as personal protective equipment

Eye/face protection

Tightly fitting safety glasses with side shields.

Hand protection

Protect skin by using skin protective cream. Wear suitable gloves.

When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits.

The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances.

Recommendation direct, prolonged contact: Protective index 6, penetration time > 480 min, e.g. nitrile rubber 0.4 mm

penetration time (maximum wearing period): <8h

Skin protection

Full cover clothing covering arms and legs.

Respiratory protection

Use protective filter mask in case of short-term and low exposure; in case of intense or longer exposure, use respiratory protection device operating independently from circulating air.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state:	liquid	
Colour:	brown	
Odour:	characteristic	
Odour threshold:	no data available	
Melting point/freezing point:		not determined
Boiling point or initial boiling point and boiling range:		57 °C
Flammability:		not determined
Lower explosion limits:		3,1 vol. %
Upper explosion limits:		16,0 vol. %
Flash point:		-13 °C
Auto-ignition temperature:		not determined
Decomposition temperature:		not determined
pH-Value:		not determined

Safety Data Sheet

according to Regulation (EC) No 1907/2006

FDT Dachbahnenkleber

Revision: 09.04.2025

Product code: FDT-001

Page 7 of 13

Viscosity / kinematic:	not determined
Water solubility:	Not mixable and/or hard to mix.
Solubility in other solvents	
no data available	
Dissolution rate:	no data available
Partition coefficient n-octanol/water:	not determined
Dispersion stability:	no data available
Vapour pressure:	228 hPa
(at 20 °C)	
Density (at 20 °C):	1,08 g/cm ³
Relative density:	no data available
Bulk density:	not applicable
Relative vapour density:	not determined
Particle characteristics:	not applicable

9.2. Other information**Information with regard to physical hazard classes**

Explosive properties

The product is not explosive, however, formation of explosive mixtures are possible.

Self-ignition temperature

Gas:

not determined

Oxidizing properties

not determined

Other safety characteristics

Solvent content:

12%

Solid content:

88%

Viscosity / dynamic:

8500 mPa·s

(at 20 °C)

Further Information

No further data available.

SECTION 10: Stability and reactivity**10.1. Reactivity**

No dangerous reactivity under regular conditions.

10.2. Chemical stability

The product is stable under regular conditions.

10.3. Possibility of hazardous reactions

No known hazardous reactions.

10.4. Conditions to avoid

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

10.5. Incompatible materials

Oxidising agent

10.6. Hazardous decomposition products

Thermal decomposition can lead to harmful gases and vapours.

SECTION 11: Toxicological information**11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008****Acute toxicity**

Based on available data, the classification criteria are not met.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

FDT Dachbahnenkleber

Revision: 09.04.2025

Product code: FDT-001

Page 8 of 13

ATEmix calculated

ATE (oral) > 2000 mg/kg; ATE (dermal) > 2000 mg/kg; ATE (inhalation vapour) > 50 mg/l; ATE (inhalation dust/mist) > 12,5 mg/l

CAS No	Chemical name					
	Exposure route	Dose	Species	Source	Method	
9016-87-9	Diphenylmethanediisocyanate - Isomers & Homologues					
	inhalation vapour	ATE 11 mg/l				
	inhalation dust/mist	ATE 1,5 mg/l				
141-78-6	ethyl acetate					
	oral	LD50 4100 mg/kg	Mouse			
	dermal	LD50 >20000 mg/kg	Rabbit			

Irritation and corrosivity

Skin corrosion/irritation: Causes skin irritation.

Serious eye damage/eye irritation: Causes serious eye irritation.

Sensitising effects

May cause allergy or asthma symptoms or breathing difficulties if inhaled. (Diphenylmethanediisocyanate - Isomers & Homologues)

May cause an allergic skin reaction. (Diphenylmethanediisocyanate - Isomers & Homologues)

Contains isocyanates. May produce an allergic reaction.

Carcinogenic/mutagenic/toxic effects for reproduction

Suspected of causing cancer. (Diphenylmethanediisocyanate - Isomers & Homologues)

Germ cell mutagenicity: Based on available data, the classification criteria are not met.

Reproductive toxicity: Based on available data, the classification criteria are not met.

STOT-single exposure

May cause drowsiness or dizziness.

STOT-repeated exposure

May cause damage to organs through prolonged or repeated exposure. (Diphenylmethanediisocyanate - Isomers & Homologues)

Aspiration hazard

Based on available data, the classification criteria are not met.

11.2. Information on other hazards

Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to humans as no components meets the criteria.

SECTION 12: Ecological information

12.1. Toxicity

Based on available data, the classification criteria are not met.

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h] [d]	Species	Source	Method
141-78-6	ethyl acetate					
	Acute fish toxicity	LC50 230 mg/l	96 h	Pimephales promelas		
	Acute crustacea toxicity	EC50 165 mg/l	48 h	Daphnia magna		
	Algae toxicity	NOEC >100 mg/l	3 d	Desmodesmus subspicatus		

12.2. Persistence and degradability

Safety Data Sheet

according to Regulation (EC) No 1907/2006

FDT Dachbahnenkleber

Revision: 09.04.2025

Product code: FDT-001

Page 9 of 13

No data available.

12.3. Bioaccumulative potential

No data available.

12.4. Mobility in soil

No data available.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

12.7. Other adverse effects

No data available.

SECTION 13: Disposal considerations**13.1. Waste treatment methods****Disposal recommendations**

The allocation of waste identity numbers/waste descriptions must be carried out according to the EEC, specific to the industry and process.

Dispose of waste according to applicable legislation.

List of Wastes Code - residues/unused products

080409 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU of adhesives and sealants (including waterproofing products); waste adhesives and sealants containing organic solvents or other hazardous substances; hazardous waste

List of Wastes Code - used product

080409 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU of adhesives and sealants (including waterproofing products); waste adhesives and sealants containing organic solvents or other hazardous substances; hazardous waste

List of Wastes Code - contaminated packaging

150110 WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED; packaging (including separately collected municipal packaging waste); packaging containing residues of or contaminated by hazardous substances; hazardous waste

Contaminated packaging

Non-contaminated packages may be recycled. Handle contaminated packages in the same way as the substance itself.

SECTION 14: Transport information**Land transport (ADR/RID)**

<u>14.1. UN number or ID number:</u>	UN 1133
<u>14.2. UN proper shipping name:</u>	Adhesives
<u>14.3. Transport hazard class(es):</u>	3
<u>14.4. Packing group:</u>	III
Hazard label:	3

Safety Data Sheet

according to Regulation (EC) No 1907/2006

FDT Dachbahnenkleber

Revision: 09.04.2025

Product code: FDT-001

Page 10 of 13



Classification code: F1
 Special Provisions: 640H
 Limited quantity: 5 L
 Excepted quantity: E1
 Transport category: 3
 Hazard No: 33
 Tunnel restriction code: D/E

Inland waterways transport (ADN)

14.1. UN number or ID number: UN 1133
14.2. UN proper shipping name: Adhesives
14.3. Transport hazard class(es): 3
14.4. Packing group: III
 Hazard label: 3



Classification code: F1
 Special Provisions: 640H
 Limited quantity: 5 L
 Excepted quantity: E1

Marine transport (IMDG)

14.1. UN number or ID number: UN 1133
14.2. UN proper shipping name: Adhesives
14.3. Transport hazard class(es): 3
14.4. Packing group: III
 Hazard label: 3



Marine pollutant: Nein
 Special Provisions: 223, 955
 Limited quantity: 5 L
 Excepted quantity: E1
 EmS: F-E, S-D

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number or ID number: UN 1133
14.2. UN proper shipping name: Adhesives
14.3. Transport hazard class(es): 3
14.4. Packing group: III
 Hazard label: 3



Special Provisions: A3
 Limited quantity Passenger: 10 L
 Passenger LQ: Y344
 Excepted quantity: E1
 IATA-packing instructions - Passenger: 355

Safety Data Sheet

according to Regulation (EC) No 1907/2006

FDT Dachbahnenkleber

Revision: 09.04.2025

Product code: FDT-001

Page 11 of 13

IATA-max. quantity - Passenger:	60 L
IATA-packing instructions - Cargo:	366
IATA-max. quantity - Cargo:	220 L

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No

14.6. Special precautions for user

No special precautions known.

14.7. Maritime transport in bulk according to IMO instruments

not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 40, Entry 75

Information according to Directive 2012/18/EU (SEVESO III): P5c FLAMMABLE LIQUIDS

Additional information

Regulation (EC) No. 1005/2009 on substances that lead to the depletion of the ozone layer: not applicable

Regulation (EC) No. 648/2004 [Detergents regulation]: not applicable

Regulation (EC) No 2019/1021 on persistent organic pollutants: not applicable

Regulation (EC) No 649/2012 of the European Parliament and of the Council concerning the export and import of dangerous chemicals: This mix contains no chemicals that are subject to the export notification procedures (annex 1).

This mixture contains the following substances of very high concern (SVHC) which are included in the Candidate List according to Article 59 of REACH: none

This mixture contains the following substances of very high concern (SVHC) which are subject to authorisation according to Annex XIV of REACH: none

National regulatory information

Employment restrictions: Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC). Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers. Observe employment restrictions for women of child-bearing age.

Water hazard class (D): 1 - slightly hazardous to water

Additional information

Observe in addition any national regulations!

15.2. Chemical safety assessment

For the following substances of this mixture a chemical safety assessment has been carried out:

methyl acetate

ethyl acetate

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane

SECTION 16: Other information

Changes

This data sheet contains changes from the previous version in section(s): 2,3,4,6,8,9,11,12,13,15,16.

Version 1,00 - Creation - 22.04.2014

Version 1,01 - Classification/Labeling according Regulation No.1272/2008 (GHS/CLP) and general revision - 27.07.2015

Version 1,02 - General update - 12.01.2021

Safety Data Sheet

according to Regulation (EC) No 1907/2006

FDT Dachbahnenkleber

Revision: 09.04.2025

Product code: FDT-001

Page 12 of 13

Version 1,03 - General update - 09.04.2025

Abbreviations and acronyms

Flam. Liq. 2: Flammable liquids, hazard category 2
Acute Tox. 4: Acute toxicity, hazard category 4
Asp. Tox. 1: Aspiration hazard, hazard category 1
Skin Irrit. 2: Skin irritation, hazard category 2
Eye Irrit. 2: Eye irritation, hazard category 2
Resp. Sens. 1: Respiratory sensitisation, hazard category 1
Skin Sens. 1: Skin sensitisation, hazard category 1
Carc. 2: Carcinogenicity, hazard category 2
STOT SE 3: Specific target organ toxicity - single exposure, hazard category 3
STOT RE 2: Specific target organ toxicity - repeated exposure, hazard category 2
Aquatic Chronic 2: Hazardous to the aquatic environment, long-term hazard category: Chronic 2
ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)
AwSV: Ordinance on Installations for Handling Substances Hazardous to Water
BImSchV (Fed.Imm.Prot.Act): Directive on the Implementation of the Federal Immission Protection Act
CAS: Chemical Abstracts Service
DIN: Norm of the Deutsche Institut für Normung (German Institute for Standardization)
EC: Effective Concentration
EG: European Community (Europäische Gemeinschaft)
EN: European Norm
IATA: International Air Transport Association
IBC Code: International Code for the Construction and Equipment of ships carrying Dangerous Chemicals in Bulk
ICAO: International Civil Aviation Organization
IMDG: International Maritime Code for Dangerous Goods
ISO: Norm of the International Standards Organization
CLP: Classification, Labeling, Packaging
IUCLID: International Uniform Chemical Information Database
LC: Lethal concentration
LD: Lethal dose
log Kow: Octanol/water partition coefficient
MARPOL: Maritime Pollution Convention = Convention for the Prevention of Maritime Pollution from Ships
OECD: Organisation for Economic Co-operation and Development
PBT: Persistent, bio-cumulative, toxic
RID: Regulation Concerning the International Transport of Dangerous Goods by Rail
TRGS: Technische Regeln für Gefahrstoffe
UN: United Nations
VOC: Volatile Organic Compounds
vPvB: very persistent and very bio-cumulative
WGK: German Water Hazard Class
GHS: Globally Harmonized System of Classification and Labelling of Chemicals
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
DNEL: Derived No Effect Level
PNEC: Predicted No Effect Concentration
TLV: Threshold Limiting Value
STOT: Specific Target Organ Toxicity

Safety Data Sheet

according to Regulation (EC) No 1907/2006

FDT Dachbahnenkleber

Revision: 09.04.2025

Product code: FDT-001

Page 13 of 13

Classification for mixtures and used evaluation method according to Regulation (EC) No 1272/2008 [CLP]

Classification	Classification procedure
Flam. Liq. 2; H225	On basis of test data
Carc. 2; H351	Calculation method
Skin Irrit. 2; H315	Calculation method
Eye Irrit. 2; H319	Calculation method
Resp. Sens. 1; H334	Calculation method
Skin Sens. 1; H317	Calculation method
STOT SE 3; H336	Calculation method
STOT RE 2; H373	Calculation method

Relevant H and EUH statements (number and full text)

H225	Highly flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H351	Suspected of causing cancer.
H373	May cause damage to organs through prolonged or repeated exposure.
H411	Toxic to aquatic life with long lasting effects.
EUH066	Repeated exposure may cause skin dryness or cracking.
EUH204	Contains isocyanates. May produce an allergic reaction.

Further Information

The information given in this safety data sheet is to describe the product's safety regulations. It is not for guaranteeing certain characteristics and is based on today's knowledge. The safety data sheet was generated upon information of pre-suppliers by:

asseso AG, Ottostraße 1, 63741, Aschaffenburg, Germany

Phone: +49 (0)6021 - 1 50 86-0, Fax: +49 (0)6021 - 1 50 86-77, E-Mail: eu-sds@asseso.eu, www.asseso.eu

(The data for the relevant ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)