



Sustainability data sheet

Rhenofol® CV - Roofing membrane for mechanically fixed roof systems

Rhenofol CV is a light grey roofing membrane made of soft polyvinyl chloride (PVC-P) according to EN 13956, not compatible with bitumen (NB), reinforced (V) with polyester fabric (PG), application type DE – PVC-P-NB-V-PG according to TS 20.000-201. Rhenofol CV is a two-layer roofing membrane system consisting of an upper film and a lower film, with the upper film accounting for approximately half of the roofing membrane thickness. The upper film is equipped with high-quality plasticizers, stabilizers, flame retardants and other additives throughout its entire thickness. Due to thickness of the high-quality upper film, an above-average quality and life expectancy can be achieved. Because of their excellent material properties, Rhenofol CV roofing membranes can be laid in a single layer. The seam overlaps can be closed practically by solvent welding or hot air welding.

Tests and approvals

- Evidence of an Environmental Product Declaration in the form of a product-specific EPD in accordance with ISO 14025 and EN 15804 (www.ibu-epd.com) and listed in the DGNB Navigator (www.dgnb-navigator.de) with the declaration number: EPD-FDT-20240156-IBA1-DE.
- Reaction to fire: Building material class B 2, DIN 4102, or class E according to EN 13501-1
- Testing for resistance to external fire exposure in accordance with CEN/TS 1187 and classification in accordance with EN 13501-5: Broof (t1) (for various roof structures; General Appraisal Certificates (AbP) or Classification Reports can be requested separately).
- No herbicides are used in the product
- DUBOkeur Certificate, Nibe Research BV (testing of environmental and health aspects)
- BBA Certification, British Board of Agrément
- FM approval for various roof systems
- Solar Reflectance Index (SRI) according to ASTM E 1980 in the color Rhenofol® CV white (based on RAL 9016) >105 (new material)
- FDT Flachdach Technologie GmbH is certified according to ISO 14001 (environmental management)

Product features

- Does not contain bitumen
- no stabilizers based on lead, cadmium or organic tin compounds > 0.1 %
- no fire retardants containing halogens or orthophosphoric acid
- No SVHC substances > 0.1 %
- Post-consumer recycled content: 0 %
- Pre-consumer recycled content: approx. 10 % (only in the lower film)
- Extremely weather-resistant, even without additional surface protection
- Resistant to atmospheric conditions, e.g. UV rays, as well as industrial and heating exhaust gases
- Extremely high UV resistance (≥ 7,500 hours) according to EN 1297
- High resistance to natural ageing
- A building product designed for easy dismantling
- Once the product has served its purpose, the product can be sent for plastic recycling or thermal recovery.
- System-specific repairs are possible over the entire service life
- Low surface weight of only 1.85 kg/m² (thickness 1.5 mm)
- Listing on the portals www.ibu-epd.com and www.dgnb-navigator.de with the declaration number: EPD-FDT-20240156-IBA1-DE

Building certifications (DGNB, BNB, QNG, BREEAM, LEED):

DGNB (Version 2018)

(Deutsche Gesellschaft für Nachhaltiges Bauen e. V.
[(German Sustainable Construction Association)])

Relevant requirements according to DGNB criterion,
ENV1.2 "Risks to the local environment":

1. Criteria matrix row number 31b:
Sheet-like seals (DGNB version 2018, see Annex 1
criteria matrix)
Requirement: MCCPP compounds $\leq 1 \text{ mg/m}^2$,
for green roofs $\leq 47 \text{ mg/m}^2$

Quality level 1: fulfilled
Quality level 2: fulfilled
Quality level 3: fulfilled
Quality level 4: fulfilled
2. Criteria matrix row number 36:
Synthetic foils on the roof and foundation
(DGNB version 2018, see Appendix 1 Criteria matrix)
Requirement: Free of lead and organotin compounds
(manufacturer's declaration: content $< 0.1 \%$)

Quality level 1: fulfilled
Quality level 2: fulfilled
Quality level 3: fulfilled
Quality level 4: fulfilled
3. Criteria matrix row number 44:
Synthetic products
(DGNB version 2018, see Annex 1 Criteria matrix)
Requirement: No SVHC substances*
(manufacturer's declaration: content $< 0.1 \%$)

Quality level 1: -
Quality level 2: -
Quality level 3: fulfilled
Quality level 4: fulfilled

BNB (Version 2015)

(Bewertungssystem Nachhaltiges Bauen für Büro-
und Verwaltungsgebäude [Sustainable building
assessment system of office and administration
buildings])

Relevant requirements according to BNB
criterion 1.1.6 "Risks to the local environment":

The BNB system version sets out requirements
for PVC construction products:

1. BNB_BN 1.1.6 Annex 1, row number 29:
Building products made of plastic (PVC)
Requirement: no cadmium and lead stabilizers;
for soft PVC: phthalate plasticizers toxic to
reproduction $< 0.1 \%$ (see Appendix 2, E)

Quality level 1: fulfilled
Quality level 2: fulfilled
Quality level 3: fulfilled
Quality level 4: fulfilled
Quality level 5: fulfilled
2. BNB_BN 1.1.6 Annex 1, row number 37:
Biocides - waterproofing membranes - polymer
bitumen membranes requirement: No addition of
root-inhibiting active substances, such as
Mecoprop.

Quality level 1: fulfilled
Quality level 2: fulfilled
Quality level 3: fulfilled
Quality level 4: fulfilled
Quality level 5: fulfilled

Rhenofol® CV does not contain any root-inhibiting active
substances, such as Mecoprop.

* SVHC = Substance of Very High Concern.

QNG (Qualitätssiegel Nachhaltiges Gebäude [Sustainable Building Certification])

Within the framework of the Bundesförderung für effiziente Gebäude (BEG) [Federal Funding for Efficient Buildings] the state has subsidized sustainability aspects through a dedicated "NH Class" since 1 July 2021.

The proof required for the granting of the subsidy is provided by the award of the building-related QNG.

Relevant requirements according to the QNG criteria catalogue, Annex 313 dated 14 September 2023 "Avoidance of harmful substances in building materials":

The QNG criteria catalog sets out requirements solely for PVC roofing membranes.

Rhenofol® CV fulfills the requirements:

1. Requirement: no intentionally added cadmium compounds > 0.01 % (w/w) and no tin or lead stabilizers > 0.1 % (w/w);
Classification: fulfilled
2. Requirement for plasticized PVC: no phthalate plasticizers that are toxic to reproduction < 0.1 %
Classification: fulfilled

Special features:

Rhenofol® CV does not contain any root-inhibiting active ingredients, such as Mecoprop or similar herbicides.

BREEAM - International New Construction (Building Research Establishment Environmental Assessment Method)

Materials: Mat 01 Life Cycle impacts

Requirement: Availability of a valid and standard-compliant EPD

Classification: A valid and standard-compliant product EPD is available

Materials: Mat 03 Responsible sourcing of Construction products

Requirement: Certifications are in place for responsible procurement or environmental management systems.

Classification: FDT Flachdach Technologie GmbH is certified according to ISO 14001 (environmental management).

LEED 4.1 (Leadership in Energy and Environmental Design)

Category "Material & Resources"

Requirement: Criterion MRc2 Environmental Product Declaration (Environmental Product Declarations)

Classification: The product has a product-specific EPD

Requirement: Criterion MRc3 Recycled content (Sourcing of Raw Materials)

Classification: Pre-consumer: 10 % on average (lower film),
Post-consumer: 0 % on average

Requirement: Criterion MRc4 material components (Material Ingredients)

Classification: This product is a product as defined in the EC Regulation No. 1907/2006 (REACH). Based on our current knowledge, the product does not contain any substances in concentrations exceeding 0.1% by weight, that are listed in Annex XIV or Annex XVII of the REACH regulation or on the candidate list published by the European Chemicals Agency.

Category: "Sustainable Sites"

Requirement: Criterion SS5 Heat reduction (Heat Island Reduction)

Classification: Rhenofol® CV in the color "white" (based on RAL 9016) has a Solar Reflectance Index (SRI) >105 (new product) in accordance with ASTM E 1980.

FDT – Legal Notice

We refer emphatically to the fact, that all details mentioned, especially the application and utilization recommendation for the products and their system accessories, have been developed under normal conditions, and based on our knowledge and experience. It is also assumed that the products will be stored and used correctly. Due to variations in materials, substrates and working conditions, no guarantee of the outcome of the work or liability, regardless of any legal relationship, can be inferred from these instructions or from any verbal statement. In the event of any claim that FDT has acted with intent or gross negligence, the user must provide proof that they have supplied FDT in writing with all necessary information and details for a proper and relevant assessment, in a timely, complete and accurate manner. The user is responsible for ensuring that the products are suitable for the given application. FDT reserves the right to make changes to the product specifications. Property rights of third parties are to be considered. In addition, our respective terms and conditions of sale and delivery apply. The latest published or available version of the product data sheet, which can be requested directly from FDT, is also binding. All information, technical specifications and drawings are based on the current state of technology and our experience.

Technical changes reserved. As of 13th October 2026. © 2026 FDT Flachdach Technologie GmbH, Mannheim, Germany

FDT Flachdach Technologie GmbH

Eisenbahnstraße 6 – 8
68199 Mannheim,
Germany

Tel. +49 621-8504-0
Fax +49 621-8504-2 00
www.fdt.de